

(b) *Final containers.* Final containers used for Source Plasma, whether integrally attached or separated from the original blood container, shall not be entered prior to issuance for any purpose except for filling with the plasma. Such containers shall be uncolored and hermetically sealed, and shall permit clear visibility of the contents. Final containers and their components shall not interact with the plasma contents under conditions of storage and use so as to alter the safety, quality, purity, or potency of the plasma and shall provide adequate protection against external factors that may cause deterioration or contamination. Prior to filling, the final container shall be marked or identified by number or other symbol which will relate it directly to the donor.

(c) *Preservative.* Source Plasma shall not contain a preservative.

[38 FR 32089, Nov. 20, 1973, as amended at 41 FR 10769, Mar. 12, 1976; 50 FR 4140, Jan. 29, 1985]

§ 640.69 General requirements.

(a) *Pooling.* Two units of Source Plasma from the same donor may be pooled if such units are collected during one plasmapheresis procedure: *Provided*, That the pooling is done by a procedure that does not introduce a risk of contamination of the red blood cells and, for plasma intended for injectable products, gives maximum assurance of a sterile container of plasma.

(1) The pooling of plasma from two or more donors is not permitted in the manufacture of Source Plasma intended for manufacturing into injectable products.

(2) The pooling of plasma from two or more donors by the manufacturer of Source Plasma intended for manufacturing into noninjectable products is permitted: *Provided*, That the plasma from two or more donors is pooled after the plasma has been removed from the red blood cells, and after the red blood cell containers are sealed.

(b) *Storage.* Immediately after filling, plasma intended for manufacturing into injectable products shall be stored at a temperature not warmer than -20°C ., except for plasma collected as provided in § 640.74. Plasma intended for manufacturing into noninjectable

products may be stored at temperatures appropriate for the intended use of the final product, provided these temperatures are included in the Source Plasma license application.

(c) *Inspection.* Source Plasma intended for manufacturing into injectable products shall be inspected for evidence of thawing at the time of issuance, except that inspection of individual plasma containers need not be made if the records of continuous monitoring of the storage temperature establish that the temperature remained at -20°C or colder. If there is evidence that the storage temperature has not been maintained at -20°C or colder, the plasma may be relabeled and issued as provided in § 640.76(a).

(d) *Pilot samples.* If pilot samples are provided, they shall meet the following standards:

(1) Prior to filling, all pilot samples shall be marked or identified so as to relate them directly to the donor of that unit of plasma.

(2) All pilot samples shall be filled at the time the final product is prepared by the person who prepares the final product.

(3) All pilot samples shall be representative of the contents of the final product.

(4) All pilot samples shall be collected in a manner that does not contaminate the contents of the final container.

[38 FR 32089, Nov. 20, 1973, as amended at 41 FR 10769, Mar. 12, 1976; 41 FR 14367, Apr. 5, 1976; 50 FR 4140, Jan. 29, 1985]

§ 640.70 Labeling.

(a) In addition to the labeling requirements of § 610.62 of this chapter, and in lieu of the requirements in §§ 606.121, 610.60, and 610.61 of this chapter, the following information shall appear on the label affixed to each container of Source Plasma:

(1) The proper name of the product.

(2) The statement "Caution: For Manufacturing Use Only" for products intended for further manufacturing into injectable products, or the statement, "Caution: For Use In Manufacturing Noninjectable Products Only", for products intended for further manufacturing into noninjectable products. The statement shall follow the proper