

§ 250.914 Records.

The lessee shall compile, retain, and make available to Minerals Management Service representatives for the functional life of all platforms, the as-built structural drawings, the design assumptions and analyses, a summary of the nondestructive examination records, and the inspection results from platform inspections required by § 250.912 of this part.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29486, May 29, 1998]

Subpart J—Pipelines and Pipeline Rights-of-Way**§ 250.1000 General requirements.**

(a) Pipelines and associated valves, flanges, and fittings shall be designed, installed, operated, maintained, and abandoned to provide safe and pollution-free transportation of fluids in a manner which does not unduly interfere with other uses in the Outer Continental Shelf (OCS).

(b) An application shall be submitted to the Regional Supervisor and approval obtained prior to the installation, modification, or abandonment of a pipeline which qualifies as a lease term pipeline (see § 250.1001, Definitions) and prior to the installation of a right-of-way pipeline or the modification or relinquishment of a pipeline right-of-way.

(c)(1) Department of the Interior (DOI) pipelines, as defined in § 250.1001, must meet the requirements in §§ 250.1000 through 250.1008.

(2) A pipeline right-of-way grant holder must identify in writing to the Regional Supervisor the operator of any pipeline located on its right-of-way, if the operator is different from the right-of-way grant holder.

(3) A producing operator must identify for its own records, on all existing pipelines located on its lease or right-of-way, the specific points at which operating responsibility transfers to a transporting operator.

(i) Each producing operator must, if practical, durably mark all of its above-water transfer points by April 14, 1999 or the date a pipeline begins service, whichever is later.

(ii) If it is not practical to durably mark a transfer point, and the transfer point is located above water, then the operator must identify the transfer point on a schematic located on the facility.

(iii) If a transfer point is located below water, then the operator must identify the transfer point on a schematic and provide the schematic to MMS upon request.

(iv) If adjoining producing and transporting operators cannot agree on a transfer point by April 14, 1999, the MMS Regional Supervisor and the Department of Transportation (DOT) Office of Pipeline Safety (OPS) Regional Director may jointly determine the transfer point.

(4) The transfer point serves as a regulatory boundary. An operator may write to the MMS Regional Supervisor to request an exception to this requirement for an individual facility or area. The Regional Supervisor, in consultation with the OPS Regional Director and affected parties, may grant the request.

(5) Pipeline segments designed, constructed, maintained, and operated under DOT regulations but transferring to DOI regulation as of October 16, 1998, may continue to operate under DOT design and construction requirements until significant modifications or repairs are made to those segments. After October 16, 1998, MMS operational and maintenance requirements will apply to those segments.

(d) A pipeline which qualifies as a right-of-way pipeline (see § 250.1001, Definitions) shall not be installed until a right-of-way has been requested and granted in accordance with this subpart.

(e)(1) The Regional Supervisor may suspend any pipeline operation upon a determination by the Regional Supervisor that continued activity would threaten or result in serious, irreparable, or immediate harm or damage to life (including fish and other aquatic life), property, mineral deposits, or the marine, coastal, or human environment.

(2) The Regional Supervisor may also suspend pipeline operations or a right-of-way grant if the Regional Supervisor determines that the lessee or right-of-

§ 250.1001

30 CFR Ch. II (7-1-00 Edition)

way holder has failed to comply with a provision of the Act or any other applicable law, a provision of these or other applicable regulations, or a condition of a permit or right-of-way grant.

(3) The Secretary of the Interior (Secretary) may cancel a pipeline permit or right-of-way grant in accordance with 43 U.S.C. 1334(a)(2). A right-of-way grant may be forfeited in accordance with 43 U.S.C. 1334(e).

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29486, May 29, 1998; 63 FR 34597, June 25, 1998; 63 FR 43880, Aug. 17, 1998]

§ 250.1001 Definitions.

Terms used in this subpart shall have the meanings given below:

DOI pipeline refers to a pipeline extending upstream from a point on the OCS where operating responsibility transfers from a producing operator to a transporting operator.

Lease term pipelines are those pipelines owned and operated by a lessee or operator and are wholly contained within the boundaries of a single lease, unitized leases, or contiguous (not cornering) leases of that lessee or operator.

Pipelines are the piping, risers, and appurtenances installed for the purpose of transporting oil, gas, sulphur, and produced water. (Piping confined to a production platform or structure is covered in Subpart H, Production Safety Systems, and is excluded from this subpart.)

Right-of-way pipelines are those pipelines which—

(a) Are contained within the boundaries of a single lease or group unitized leases but are not owned and operated by the lessee or operator of that lease or unit,

(b) Are contained within the boundaries of contiguous (not cornering) leases which do not have a common lessee or operator,

(c) Are contained within the boundaries of contiguous (not cornering) leases which have a common lessee or operator but are not owned and operated by that common lessee or operator, or

(d) Cross any portion of an unleased block(s).

[53 FR 10690, Apr. 1, 1998. Redesignated at 63 FR 29479, May 29, 1998, as amended at 63 FR 43881, Aug. 17, 1998]

§ 250.1002 Design requirements for DOI pipelines.

(a) The internal design pressure for steel pipe shall be determined in accordance with the following formula:

$$P = \frac{2(S)(t)}{D} \times (F)(E)(T)$$

For limitations see section 841.121 of American National Standards Institute (ANSI) B31.8 where—

P=Internal design pressure in pounds per square inch (psi).

S=Specified minimum yield strength, in psi, stipulated in the specification under which the pipe was purchased from the manufacturer or determined in accordance with section 811.253(h) of ANSI B31.8.

D=Nominal outside diameter of pipe, in inches.

t=Nominal wall thickness, in inches.

F=Construction design factor of 0.72 for the submerged component and 0.60 for the riser component.

E=Longitudinal joint factor obtained from Table 841.1B of ANSI B31.8. (See also section 811.253(d)).

T=Temperature derating factor obtained from Table 841.1C of ANSI B31.8.

(b)(1) Pipeline valves shall meet the minimum design requirements of American Petroleum Institute (API) Spec 6A, API Spec 6D, or the equivalent. A valve may not be used under operating conditions that exceed the applicable pressure-temperature ratings contained in those standards.

(2) Pipeline flanges and flange accessories shall meet the minimum design requirements of ANSI B16.5, API Spec 6A, or the equivalent. Each flange assembly must be able to withstand the maximum pressure at which the pipeline is to be operated and to maintain its physical and chemical properties at any temperature to which it is anticipated that it might be subjected in service.

(3) Pipeline fittings shall have pressure-temperature ratings based on stresses for pipe of the same or equivalent material. The actual bursting