

Minerals Management Service, Interior

§ 250.416

ram, blind ram, and blind-shear ram preventers.

(4) A casing program including the following:

(i) Casing size, weight, grade, type of connection, and setting depth;

(ii) Casing design safety factors for tension, collapse, and burst with the assumptions made to arrive at these values; and

(iii) In areas containing permafrost, casing programs that incorporate setting depths for conductor and surface casing based on the anticipated depth of the permafrost at the proposed well location and which utilize the current state-of-the-art methods to safely drill and set casing. The casing program shall provide protection from thaw subsidence and freezeback effect, proper anchorage, and well control.

(5) The drilling prognosis including the following:

(i) Projected plans for coring at specified depths;

(ii) Projected plans for logging;

(iii) Estimated depths to the top of significant marker formations; and

(iv) Estimated depths at which encounters with significant porous and permeable zones containing fresh water, oil, gas, or abnormally pressured water are expected.

(6) A cementing program including type and amount of cement in cubic feet to be used for each casing string.

(7) A mud program including the minimum quantities of mud and mud materials, including weight materials, to be kept at the site.

(8) A directional survey program for directionally drilled wells.

(9) A plot of the estimated pore pressures and formation fracture gradients and the proposed mud weights and casing setting depths on the same sheet.

(10) A H₂S Contingency Plan, if applicable, and not submitted previously.

(11) Such other information as may be required by the District Supervisor.

(g) Public information copies of the APD shall be submitted in accordance with § 250.190 of this part.

[53 FR 10690, Apr. 1, 1988, as amended at 58 FR 49928, Sept. 24, 1993. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998; 64 FR 72794, Dec. 28, 1999]

§ 250.415 Sundry notices and reports on wells.

(a) Notices of the lessee's intention to change plans, make changes in major drilling equipment, deepen or plug back a well, or engage in similar activities and subsequent reports pertaining to such operations shall be submitted to the District Supervisor on Form MMS-124, Sundry Notices and Reports on Wells. Prior to commencing operations, written approval must be received from the District Supervisor unless oral approval is obtained.

(b) The Form MMS-124 submitted shall contain a detailed statement of the proposed work that will materially change from the approved work described in the APD. Information submitted shall include the present status of the well, including the production string or last string of casing, the well depth, the present production zones and productive capability, and all other information specified on Form MMS-124. Within 30 days after completion of the work, a subsequent detailed report of all the work done and the results obtained shall be submitted.

(c) A Form MMS-124 with a plat, certified by a registered land surveyor, shall be filed as soon as the well's final surveyed surface location, water depth, and the rotary kelly bushing elevation have been determined.

(d) Public information copies of Sundry Notices and Reports on Wells shall be submitted in accordance with § 250.190 of this part.

[53 FR 10690, Apr. 1, 1988, as amended at 58 FR 49928, Sept. 24, 1993. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998; 64 FR 72794, Dec. 28, 1999]

§ 250.416 Well records.

(a) Complete and accurate records for each well and of all well operations shall be retained for a period of 2 years at the lessee's field office nearest the OCS facility or at another location conveniently available to the District Supervisor. The records shall contain a description of any significant malfunction or problem; all the formations penetrated; the content and character of oil, gas, and other mineral deposits and water in each formation; the kind, weight, size, grade, and setting depth of casing; all well logs and surveys run