

(ii) API Spec Q1, Specification for Quality Programs.

(3) All SSV's and USV's must meet the technical specifications of API Spec 6A and 6AV1. All SSSV's must meet the technical specifications of API Spec 14A.

(b) *Use of noncertified SPPE.* (1) Before April 1, 1998, you may continue to use and install noncertified SPPE if it was in your inventory as of April 1, 1988, and was included in a list of noncertified SPPE submitted to MMS prior to August 29, 1988.

(2) On or after April 1, 1998:

(i) You may not install additional noncertified SPPE; and

(ii) When noncertified SPPE that is already in service requires offsite repair, remanufacturing, or hot work such as welding, you must replace it with certified SPPE.

(c) *Recognizing other quality assurance programs.* The MMS will consider recognizing other quality assurance programs covering the manufacture of SPPE. If you want MMS to evaluate other quality assurance programs, submit relevant information about the program and reasons for recognition by MMS to the Chief, Engineering and Operations Division; Minerals Management Service; Mail Stop 4700; 381 Elden Street; Herndon, Virginia 20170-4817.

[62 FR 42671, Aug. 8, 1997. Redesignated at 63 FR 29479, May 29, 1998, as amended at 63 FR 37068, July 9, 1998]

#### § 250.807 Hydrogen sulfide.

Production operations in zones known to contain hydrogen sulfide (H<sub>2</sub>S) or in zones where the presence of H<sub>2</sub>S is unknown, as defined in § 250.417 of this part, shall be conducted in accordance with that section and other relevant requirements of subpart H, Production Safety Systems.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998]

### Subpart I—Platforms and Structures

#### § 250.900 General requirements.

(a) The lessee shall design, fabricate, install, use, inspect, and maintain all platforms and structures (platforms) on the Outer Continental Shelf (OCS)

to assure their structural integrity for the safe conduct of drilling, workover, and production operations, considering the specific environmental conditions at the platform location.

(b) All new fixed or bottom-founded platforms (i.e., platforms or other structures, e.g., single-well caissons, artificial islands), shall be designed, fabricated, installed, inspected, and maintained in accordance with all the requirements of this section and §§ 250.901 and 250.904 through 250.914 of this subpart. Applications submitted pursuant to § 250.901 shall require the approval by the Regional Supervisor prior to platform installation.

(c) All new platforms which meet any of the conditions listed below shall be subject to the Platform Verification Program and shall be designed, fabricated, and installed in accordance with the requirements of §§ 250.901 through 250.914 of this part.

(1) Platforms installed in water depths exceeding 400 feet,

(2) Platforms having natural periods in excess of 3 seconds,

(3) Platforms installed in areas of unstable bottom conditions,

(4) Platforms having configurations and designs which have not previously been used or proven for use in the area, or

(5) Platforms installed in seismically active areas.

(d) Major modification to any platform shall be subject to the requirements of this subpart and shall require the approval of the Regional Supervisor. Major modification means any structural changes which materially alter the approved plan or causes a major deviation from approved operations.

(e)(1) Major repairs of damage to any platform shall require the prior approval of the Regional Supervisor. Major repairs of damage means corrective operations involving structural members affecting the structural integrity of a portion or all of the platform.

(2) Under emergency conditions, repairs to primary structural elements may be made to restore an existing permitted condition without prior approval. The Regional Supervisor shall