

**§ 57.3430**

PRECAUTIONS—SURFACE ONLY

**§ 57.3430 Activity between machinery or equipment and the highwall or bank.**

Persons shall not work or travel between machinery or equipment and the highwall or bank where the machinery or equipment may hinder escape from falls or slides of the highwall or bank. Travel is permitted when necessary for persons to dismount.

PRECAUTIONS—UNDERGROUND ONLY

**§ 57.3460 Maintenance between machinery or equipment and ribs.**

Persons shall not perform maintenance work between machinery or equipment and ribs unless the area has been tested and, when necessary, secured.

**§ 57.3461 Rock bursts.**

(a) Operators of mines which have experienced a rock burst shall—

(1) Within twenty four hours report to the nearest MSHA office each rock burst which:

- (i) Causes persons to be withdrawn;
- (ii) Impairs ventilation;
- (iii) Impedes passage; or
- (iv) Disrupts mining activity for more than one hour.

(2) Develop and implement a rock burst control plan within 90 days after a rock burst has been experienced.

(b) The plan shall include—

(1) Mining and operating procedures designed to reduce the occurrence of rock bursts;

(2) Monitoring procedures where detection methods are used; and

(3) Other measures to minimize exposure of persons to areas which are prone to rock bursts.

(c) The plan shall be updated as conditions warrant.

(d) The plan shall be available to an authorized representative of the Secretary and to miners or their representatives.

**Subpart C—Fire Prevention and Control**

AUTHORITY: Sec. 101, Federal Mine Safety and Health Act of 1977, Pub. L. 91-173 as

**30 CFR Ch. I (7-1-00 Edition)**

amended by Pub. L. 95-164, 91 Stat. 1291 (30 U.S.C. 811).

**§ 57.4000 Definitions.**

The following definitions apply in this subpart.

*Booster fan.* A fan installed in the main airstream or a split of the main airstream to increase airflow through a section or sections of a mine.

*Combustible liquids.* Liquids having a flash point at or above 100 ° F (37.8 ° C). They are divided into the following classes:

Class II liquids—those having flash points at or above 100 ° F (37.8 ° C) and below 140 ° F (60 ° C).

Class IIIA liquids—those having flash points at or above 140 ° F (60 ° C) and below 200 ° F (93.4 ° C).

Class IIIB liquids—those having flash points at or above 200 ° F (93.4 ° C).

*Combustible material.* A material that, in the form in which it is used and under the conditions anticipated, will ignite, burn, support combustion, or release flammable vapors when subjected to fire or heat. Wood, paper, rubber, and plastics are examples of combustible materials.

*Escapeway.* A designated passageway by which persons can leave an underground mine.

*Fire resistance rating.* The time, in minutes or hours, that an assembly of materials will retain its protective characteristics or structural integrity upon exposure to fire.

*Flame spread rating.* The numerical designation that indicates the extent flame will spread over the surface of a material during a specified period of time.

*Flammable gas.* A gas that will burn in the normal concentrations of oxygen in the air.

*Flammable liquid.* A liquid that has a flash point below 100 ° F (37.8 ° C), a vapor pressure not exceeding 40 pounds per square inch (absolute) at 100 ° F (37.8 ° C), and is known as a Class I liquid.

*Flash point.* The minimum temperature at which sufficient vapor is released by a liquid to form a flammable vapor-air mixture near the surface of the liquid.

*Main fan.* A fan that controls the entire airflow of an underground mine or