

Environmental Protection Agency

§ 409.51

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) Any cane sugar factory continuously discharging both barometric condenser cooling water and other process waste waters shall meet the following limitations. The BOD₅ limitation is determined by the addition of the net BOD₅ attributable to the barometric condenser cooling water to that amount of BOD₅ attributable to the treated process waste water. The TSS limitation is that amount of TSS attributable to the treated process waste water, excluding barometric condenser cooling water.

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kkg of gross cane)	
BOD ₅	1.14	0.63
TSS	1.41	0.47
pH	(¹)	(¹)
	English units (lb/1,000 lb of gross cane)	
BOD ₅	1.14	0.63
TSS	1.41	0.47
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

(b) Any cane sugar factory employing waste stabilization where all or a portion of the waste water discharge is stored for the entire grinding season shall meet the following limitations. The BOD₅ limitation is determined by the addition of the net BOD₅ attributable to the barometric condenser cooling water to that amount of BOD₅ attributable to the treated process waste water. The TSS limitation is that amount of TSS attributable to the treated process waste water, excluding barometric condenser cooling water.

Effluent characteristic	Effluent limitations, the total of the daily values for the entire discharge period shall not exceed—	
	Metric units (kg/kkg of gross cane)	
BOD ₅	0.63.	
TSS	0.47.	

Effluent characteristic	Effluent limitations, the total of the daily values for the entire discharge period shall not exceed—
pH	Within the range 6.0 to 9.0.
	English units (lb/1,000 lb of gross cane)
BOD ₅	0.63.
TSS	0.47.
pH	Within the range 6.0 to 9.0.

[40 FR 8503, Feb. 27, 1975, as amended at 60 FR 33950, June 29, 1995]

§ 409.47 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 409.42 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24999, July 9, 1986]

Subpart E—Florida and Texas Raw Cane Sugar Processing Subcategory

SOURCE: 40 FR 8503, Feb. 27, 1975, unless otherwise noted.

§ 409.50 Applicability; description of the Florida and Texas raw cane sugar processing subcategory.

The provisions of this subpart are applicable to discharges resulting from the processing of sugar cane into a raw sugar product for those cane sugar factories located in the states of Florida and Texas.

§ 409.51 Specialized definitions.

For the purpose of this subpart:

- (a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.
- (b) [Reserved]