

**§ 410.13**

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of wool	
BOD5 .....	10.6	5.3
COD .....	138.0	69.0
TSS .....	32.2	16.1
Oil and grease .....	7.2	3.6
Sulfide .....	0.20	0.10
Phenol .....	0.10	0.05
Total chromium .....	0.10	0.05
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0 at all times.

(b) Additional allocations equal to the effluent limitations established in paragraph (a) of this section are allowed any existing point source subject to such effluent limitations that scours wool through "commission scouring" as defined in § 410.11.

**§ 410.13 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

Pollutant or pollutant property	BAT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of wool	
COD .....	138.0	69.0
Sulfide .....	0.20	0.10
Phenols .....	0.10	0.05
Total chromium .....	0.10	0.05

(b) Additional allocations equal to the effluent limitations established in paragraph (a) of this section are allowed any existing point source subject to such effluent limitations that scours wool through "commission scouring" as defined in § 410.11.

**40 CFR Ch. I (7-1-00 Edition)**

**§ 410.14 Pretreatment standards for existing sources (PSES).**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

**§ 410.15 New source performance standards (NSPS).**

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of wool	
BOD5 .....	3.6	1.9
COD .....	52.4	33.7
TSS .....	30.3	13.5
Sulfide .....	0.20	0.10
Phenols .....	0.10	0.05
Total chromium .....	0.10	0.05
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0 at all times.

Note: Additional allocations for "commission scouring" are not available to new sources.

**§ 410.16 Pretreatment standards for new sources (PSNS).**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

**§ 410.17 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]**

**Subpart B—Wool Finishing Subcategory**

**§ 410.20 Applicability; description of the wool finishing subcategory.**

The provisions of this subpart are applicable to process wastewater discharges resulting from the following types of textile mills: wool finishers, including carbonizing, fulling, dyeing, bleaching, rinsing, fireproofing, and other such similar processes.