

§ 415.270

SUBPART X—AMMONIUM CHLORIDE SOLVAY PROCESS

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
Ammonia (as N)	8.8	4.4
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

Subpart Y—Ammonium Hydroxide Production Subcategory [Reserved]

Subpart Z—Barium Carbonate Production Subcategory [Reserved]

Subpart AA—Borax Production Subcategory

§ 415.270 Applicability; description of the borax production subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of borax by the ore-mining process and by the Trona process.

§ 415.271 Specialized definitions. [Reserved]

§ 415.272 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters, except that residual brine and depleted liquor may be returned to the body of water from which the process brine solution was originally withdrawn.

40 CFR Ch. I (7-1-00 Edition)

§§ 415.273–415.275 [Reserved]

§ 415.276 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations are the same as specified in § 415.272.

[49 FR 33421, Aug. 22, 1984]

Subpart AB—Boric Acid Production Subcategory

§ 415.280 Applicability; description of the boric acid production subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of boric acid from ore-mined borax and from borax produced by the Trona process.

§ 415.281 Specialized definitions.

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *product* shall mean boric acid.

§ 415.282 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and using borax produced by the Trona process must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters, except that residual brine and depleted liquor may be returned to the body of water from which the process brine solution was originally withdrawn.

(b) Except as provided in 40 CFR 125.30 through 125.32, any existing point

Environmental Protection Agency

§ 415.302

source subject to this subpart and using remined borax must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

SUBPART AB—BORIC ACID MINED BORAX PROCESS

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
Arsenic	0.0028	0.0014
TSS	0.14	0.07
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

Subpart AC—Bromine Production Subcategory

§ 415.290 Applicability; description of the bromine production subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of bromine by the brine-mining process and by the Trona process.

§ 415.291 Specialized definitions. [Reserved]

§ 415.292 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters, except that residual brine and depleted liquor may be returned to the body of water from which the process

brine solution was originally withdrawn.

§§ 415.293–415.295 [Reserved]

§ 415.296 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations are the same as specified in § 415.292.

[49 FR 33421, Aug. 22, 1984]

Subpart AD—Calcium Carbonate Production Subcategory

§ 415.300 Applicability; description of the calcium carbonate production subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of calcium carbonate by the milk of lime process and by the recovery process from Solvay process wastes.

§ 415.301 Specialized definitions.

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *product* shall mean calcium carbonate.

§ 415.302 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and using the milk of lime process must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):