

**Environmental Protection Agency**

**§ 415.341**

standards for new sources (PSNS): The limitations are the same as specified in § 415.312.

[49 FR 33421, Aug. 22, 1984]

**Subpart AF—Carbon Dioxide Production Subcategory [Reserved]**

**Subpart AG—Carbon Monoxide and By-Product Hydrogen Production Subcategory**

**§ 415.330 Applicability; description of the carbon monoxide and by-product hydrogen production subcategory.**

The provisions of this subpart are applicable to discharges resulting from the production of carbon monoxide and by-product hydrogen by the reforming process.

**§ 415.331 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *product* shall mean carbon monoxide plus hydrogen.

(c) The term *process wastewater* means any water which, during manufacturing or processing, comes into direct contact with or results from the production or use of any raw material, intermediate product, finished product, by-product, or waste product. The term “process wastewater” does not include contaminated nonprocess wastewater, as defined below.

(d) The term *process wastewater pollutants* means pollutants present in process wastewater.

(e) The term *contaminated nonprocess wastewater* shall mean any water which, during manufacturing or processing, comes into incidental contact with any raw material, intermediate product, finished product, by-product or waste product by means of (1) rainfall runoff; (2) accidental spills; (3) accidental leaks caused by the failure of process equipment, which are repaired within the shortest reasonable time not to exceed 24 hours after discovery; and (4) discharges from safety showers and related personal safety equipment:

Provided, that all reasonable measures have been taken (i) to prevent, reduce and control such contact to the maximum extent feasible; and (ii) to mitigate the effects of such contact once it has occurred.

**§ 415.332 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

**SUBPART AG—CARBON MONOXIDE**

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kgg (or pounds per 1,000 lb) of product	
COD .....	0.50	0.25
TSS .....	0.12	0.060
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

**Subpart AH—Chrome Pigments Production Subcategory**

**§ 415.340 Applicability; description of the chrome pigments production subcategory.**

This subpart applies to discharges to waters of the United States and introduction of pollutants into publicly owned treatment works resulting from the production of chrome pigments.

**§ 415.341 Specialized definitions.**

For the purposes of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *chrome pigments* means chrome yellow, chrome orange, molybdate chrome orange, anhydrous and hydrous chromium oxide, chrome green, and zinc yellow.