

§419.14

40 CFR Ch. I (7-1-00 Edition)

Pollutant or pollutant property	BAT effluent limitations for ballast water	
	Maximum for any 1 day	Average or daily values for 30 consecutive days shall not exceed
COD <sup>1</sup> .....	Metric units (kilograms per cubic meter of flow)	
	0.47	0.24
COD <sup>1</sup> .....	English units (pounds per 1,000 gal of flow)	
	3.9	2.0

<sup>1</sup>In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1,000 mg/l (1,000 ppm), the Regional Administrator may substitute TOC as a parameter in lieu of COD Effluent limitations for TOC shall be based on effluent data from the plant correlating TOC to BOD<sub>5</sub>.

If in the judgment of the Regional Administrator, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations on BOD<sub>5</sub>.

(e) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by paragraph (b) of this section. Once-through cooling water may be discharged with a total organic carbon concentration not to exceed 5 mg/l.

(f) *Effluent limitations for contaminated runoff.* The following effluent limitations constitute the quantity and quality of pollutants or pollutant properties controlled by this paragraph and attributable to contaminated runoff, which may be discharged after the application of the best available technology economically achievable by a point source subject to this subpart.

(1) If wastewater consists solely of contaminated runoff and is not commingled or treated with process wastewater, it may be discharged if it does not exceed 110 mg/l total organic carbon (TOC) based upon an analysis of any single grab or composite sample.

(2) If contaminated runoff is commingled or treated with process wastewater, or if wastewater consisting solely of contaminated runoff which exceeds 110 mg/l TOC is not commingled or treated with any other type of wastewater, the quantity of pollutants discharged shall not exceed the quantity determined by multiplying the flow of contaminated runoff as deter-

mined by the permit writer times the concentrations listed in the following table:

Pollutant or pollutant property	BAT effluent limitations for contaminated runoff	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
Phenolic compounds (4AAP) Total chromium ..... Hexavalent chromium ..... COD <sup>1</sup> .....	Metric units (kilograms per 1,000 m <sup>3</sup> of flow)	
	0.35 0.60 0.062 360.	0.17 0.21 0.028 180.
Phenolic compounds (4AAP) Total chromium ..... Hexavalent chromium ..... COD <sup>1</sup> .....	English units (pounds per 1,000 gallons of flow)	
	0.0029 0.0050 0.00052 3.0	0.0014 0.0018 0.00023 1.5

<sup>1</sup>In any case in which the applicant can demonstrate that the chloride ion concentration in the effluent exceeds 1,000 mg/l (1,000 ppm), the permitting authority may substitute TOC as a parameter in lieu of COD. A TOC effluent limitation shall be based on effluent data from the particular refinery which correlates TOC to BOD<sub>5</sub>. If in the judgement of the permitting authority, adequate correlation data are not available, the effluent limitations for TOC shall be established at a ratio of 2.2 to 1 to the applicable effluent limitations for BOD<sub>5</sub>.

[47 FR 46446, Oct. 18, 1982, as amended at 50 FR 28523, July 12, 1985; 50 FR 32414, Aug. 12, 1985]

**§419.14 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

(a) Any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
BOD <sub>5</sub> ..... TSS ..... Oil and Grease .....	Metric units (Kilograms per 1,000 m <sup>3</sup> of feedstock)	
	22.7 15.8 6.9	12.0 10.1 3.7

**Environmental Protection Agency**

**§419.14**

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (pounds per 1,000 bbl of feedstock)	
BOD <sub>5</sub> .....	8.0	4.25
TSS .....	5.6	3.6
Oil and Grease .....	2.5	1.3
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(b) The limits set forth in paragraph (a) of this section are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days.

(1) Size factor.

1,000 bbl of feedstock per stream day	Size factor
Less than 24.9 .....	1.02
25.0 to 49.9 .....	1.06
50.0 to 74.9 .....	1.16
75.0 to 99.9 .....	1.26
100 to 124.9 .....	1.38
125.0 to 149.9 .....	1.50
150.0 or greater .....	1.57

(2) Process factor.

Process configuration	Process factor
Less than 2.49 .....	0.62
2.5 to 3.49 .....	0.67
3.5 to 4.49 .....	0.80
4.5 to 5.49 .....	0.95
5.5 to 5.99 .....	1.07
6.0 to 6.49 .....	1.17
6.5 to 6.99 .....	1.27
7.0 to 7.49 .....	1.39
7.5 to 7.99 .....	1.51
8.0 to 8.49 .....	1.64
8.5 to 8.99 .....	1.79
9.0 to 9.49 .....	1.95
9.5 to 9.99 .....	2.12
10.0 to 10.49 .....	2.31
10.5 to 10.99 .....	2.51
11.0 to 11.49 .....	2.73
11.5 to 11.99 .....	2.98
12.0 to 12.49 .....	3.24
12.5 to 12.99 .....	3.53
13.0 to 13.49 .....	3.84
13.5 to 13.99 .....	4.18
14.0 or greater .....	4.36

(3) See the comprehensive example in subpart D, §419.43(b)(3).

(c) The following allocations constitute the quantity and quality of pollutants or pollutant properties con-

trolled by this paragraph and attributable to ballast, which may be discharged after the application of best conventional pollutant control technology by a point source subject to this subpart, in addition to the discharge allowed by paragraph (b) of this section. The allocation allowed for ballast water flow, as kg/cu m (lb/1000 gal), shall be based on those ballast waters treated at the refinery.

Pollutant or pollutant property	BCT Effluent limitations for ballast water	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric units (kilograms per m <sup>3</sup> of flow)	
BOD <sub>5</sub> .....	0.048	0.026
TSS .....	0.033	0.021
Oil and grease .....	0.015	0.008
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (pounds per 1000 gallons of flow)	
BOD <sub>5</sub> .....	0.40	0.21
TSS .....	0.26	0.17
Oil and grease .....	0.126	0.067
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph attributable to once-through cooling water, are excluded from the discharge allowed by paragraph (b) of this section.

(e) *Effluent limitations for contaminated runoff.* The following effluent limitations constitute the quantity and quality of pollutants or pollutant properties controlled by this paragraph and attributable to contaminated runoff which may be discharged after the application of the best conventional pollutant control technology by a point source subject to this subpart.

(1) If wastewater consists solely of contaminated runoff and is not commingled or treated with process wastewater, it may be discharged if it does not exceed 15 mg/l oil and grease based upon an analysis of any single grab or composite sample.

**§419.15**

(2) If contaminated runoff is commingled or treated with process wastewater, or if wastewater consisting solely of contaminated runoff which exceeds 15 mg/l oil and grease is not commingled or treated with any other type of wastewater, the quantity of pollutants discharged shall not exceed the quantity determined by multiplying the flow of contaminated runoff as determined by the permit writer times the concentrations listed in the following table:

Pollutant or pollutant property	BCT effluent limitations for contaminated runoff	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric units (kilograms per 1,000 m <sup>3</sup> of flow)	
BOD <sub>5</sub> .....	48.	26.
TSS .....	33.	21.
Oil and grease .....	15.	8.
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (pounds per 1,000 gallons of flow)	
BOD <sub>5</sub> .....	0.40	0.22
TSS .....	0.28	0.18
Oil and grease .....	0.13	0.067
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

[50 FR 28524, July 12, 1985]

**§419.15 Pretreatment standards for existing sources (PSES).**

Except as provided in 40 CFR 403.7 and 403.13 any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources (PSES). The following standards apply to the total refinery flow contribution to the POTW:

Pollutant or pollutant property	Pretreatment standards for existing sources maximum for any 1 day  (Milligrams per liter (mg/l))
Oil and Grease .....	100

**40 CFR Ch. I (7-1-00 Edition)**

Pollutant or pollutant property	Pretreatment standards for existing sources maximum for any 1 day
Ammonia (as N) .....	1 100

<sup>1</sup> Where the discharge to the POTW consists solely of sour waters, the owner or operator has the option of complying with this limit or the daily maximum mass limitation for ammonia set forth in § 419.13 (a) and (b).

**§419.16 Standards of performance for new sources (NSPS).**

(a) Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric units (kilograms per cubic meter of flow)	
BOD <sub>5</sub> .....	11.8	6.3
TSS .....	8.3	4.9
COD <sup>1</sup> .....	61.0	32
Oil and grease .....	3.6	1.9
Phenolic compounds .....	0.088	0.043
Ammonia as N .....	2.8	1.3
Sulfide .....	0.078	0.035
Total chromium .....	0.18	0.105
Hexavalent chromium .....	0.015	0.0068
pH .....	( <sup>2</sup> )	( <sup>2</sup> )
	English units (pounds per 1,000 gal of flow)	
BOD <sub>5</sub> .....	4.2	2.2
TSS .....	3.0	1.9
COD <sup>1</sup> .....	21.7	11.2
Oil and grease .....	1.3	0.70
Phenolic compounds .....	0.031	0.016
Ammonia as N .....	1.0	0.45
Sulfide .....	0.027	0.012
Total chromium .....	0.064	0.037
Hexavalent chromium .....	0.0052	0.0025
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> See footnote following table in § 419.13(d).

<sup>2</sup> Within the range of 6.0 to 9.0

(b) The limits set forth in paragraph (a) of this section are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days.

(1) Size factor.

1,000 bbl of feedstock per stream day	Size factor
Less than 24.9 .....	1.02
25.0 to 49.9 .....	1.06