

§ 432.26

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kilograms per 1,000 kg ELWK)	
Ammonia	0.10	0.05
	English units (pounds per 1,000 lb ELWK)	
Ammonia	0.10	0.05

(d) The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section and attributable to the dry rendering of material derived from animals slaughtered at locations other than the slaughterhouse, which may be discharged by a new source subject to the provisions of this subpart, in addition to the discharge allowed by paragraph (a) of this section and § 432.22(e):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kilograms per 1,000 kg ELWK)	
Ammonia	0.04	0.02
	English units (pounds per 1,000 lb ELWK)	
Ammonia	0.04	0.02

[39 FR 7897, Feb. 28, 1974; 39 FR 26423, July 19, 1974]

§ 432.26 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33965, June 29, 1995]

40 CFR Ch. I (7-1-00 Edition)

§ 432.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 432.22 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 25001, July 9, 1986]

Subpart C—Low-Processing Packinghouse Subcategory

§ 432.30 Applicability; description of the low-processing packinghouse subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of red meat carcasses in whole or part, by low-processing packinghouses.

§ 432.31 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term “packinghouse” shall mean a plant that both slaughters animals and subsequently processes carcasses into cured, smoked, canned or other prepared meat products.

(c) The term “low processing packinghouse” shall mean a packinghouse that processes no more than the total animals killed at that plant, normally processing less than the total kill.

(d) The term “LWK” (live weight killed) shall mean the total weight of the total number of animals slaughtered during the time to which the effluent limitations apply; i.e., during any one day or any period of thirty consecutive days.

(e) The term “ELWK” (equivalent live weight killed) shall mean the total