

§ 432.64

pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Milligrams per liter—effluent	
Ammonia	8.0 mg/l	4.0

[44 FR 50748, Aug. 29, 1979]

§ 432.64 [Reserved]

§ 432.65 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kg of finished product)	
BOD5	0.036	0.018
TSS	0.044	0.022
Oil and grease	0.012	0.006
pH	(¹)	(¹)
Fecal coliforms	(²)	(²)
	English units (lb/1,000 lb of finished product)	
BOD5	0.030	0.015
TSS	0.036	0.018
Oil and grease	0.012	0.006
pH	(¹)	(¹)
Fecal coliforms	(²)	(²)

¹ Within the range 6.0 to 9.0.
² Maximum at any time 400 mpn/100 ml.

§ 432.66 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the

40 CFR Ch. I (7-1-00 Edition)

quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

Pollutant or pollutant property	Pretreatment standard
BOD5	No limitation.
TSS	Do.
Oil and grease	Do.
pH	Do.
Fecal coliform	Do.

[40 FR 906, Jan. 3, 1975, as amended at 60 FR 33965, June 29, 1995]

§ 432.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in §401.16) in §432.62 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 25001, July 9, 1986]

Subpart G—Sausage and Luncheon Meats Processor Subcategory

SOURCE: 40 FR 907, Jan. 3, 1975, unless otherwise noted.

§ 432.70 Applicability; description of the sausage and luncheon meat processor subcategory.

The provisions of this subpart are applicable to discharges resulting from the manufacture of fresh meat cuts, sausage, bologna, and other luncheon meats by a sausage and luncheon meat processor.

§ 432.71 Specialized definitions.

For the purpose of this subpart:
 (a) Except as provided below, the general definitions, abbreviations and