

**§ 433.16**

(d) An existing source submitting a certification in lieu of monitoring pursuant to § 433.12 (a) and (b) of this regulation must implement the toxic organic management plan approved by the control authority.

(e) An existing source subject to this subpart shall comply with a daily maximum pretreatment standard for TTO of 4.57 mg/l.

(f) Compliance with the provisions of paragraph (c), (d), and (e) of this section shall be achieved as soon as possible, but not later than June 30, 1984, however metal finishing facilities which are also covered by part 420 (iron and steel) need not comply before July 10, 1985. Compliance with the provisions of paragraphs (a) and (b) of this section shall be achieved as soon as possible, but not later than February 15, 1986.

[48 FR 32485, July 15, 1983, as amended at 48 FR 41410, Sept. 15, 1983; 48 FR 43682, Sept. 26, 1983]

**§ 433.16 New source performance standards (NSPS).**

(a) Any new source subject to this subpart must achieve the following performance standards:

| NSPS                            |                             |                                  |
|---------------------------------|-----------------------------|----------------------------------|
| Pollutant or pollutant property | Maximum for any 1 day       | Monthly average shall not exceed |
|                                 | Milligrams per liter (mg/l) |                                  |
| Cadmium (T) .....               | 0.11                        | 0.07                             |
| Chromium (T) .....              | 2.77                        | 1.71                             |
| Copper (T) .....                | 3.38                        | 2.07                             |
| Lead (T) .....                  | 0.69                        | 0.43                             |
| Nickel (T) .....                | 3.98                        | 2.38                             |
| Silver (T) .....                | 0.43                        | 0.24                             |
| Zinc (T) .....                  | 2.61                        | 1.48                             |
| Cyanide (T) .....               | 1.20                        | 0.65                             |
| TTO .....                       | 2.13                        | .....                            |
| Oil and Grease .....            | 52                          | 26                               |
| TSS .....                       | 60                          | 31                               |
| pH .....                        | ( <sup>1</sup> )            | ( <sup>1</sup> )                 |

<sup>1</sup> Within 6.0 to 9.0.

(b) Alternatively, for industrial facilities with cyanide treatment, and upon agreement between a source subject to those limits and the pollution control authority, the following amenable cyanide limit may apply in place of the total cyanide limit specified in paragraph (a) of this section:

**40 CFR Ch. I (7-1-00 Edition)**

| Pollutant or pollutant property | Maximum for any 1 day       | Monthly average shall not exceed |
|---------------------------------|-----------------------------|----------------------------------|
|                                 | Milligrams per liter (mg/l) |                                  |
| Cyanide (A) .....               | 0.86                        | 0.32                             |

(c) No user subject to the provisions of this subpart shall augment the use of process wastewater or otherwise dilute the wastewater as a partial or total substitute for adequate treatment to achieve compliance with this limitation.

[48 FR 32485, July 15, 1983; 48 FR 43682, Sept. 26, 1983]

**§ 433.17 Pretreatment standards for new sources (PSNS).**

(a) Except as provided in 40 CFR 403.7, any new source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS):

| PSNS                            |                             |                                  |
|---------------------------------|-----------------------------|----------------------------------|
| Pollutant or pollutant property | Maximum for any 1 day       | Monthly average shall not exceed |
|                                 | Milligrams per liter (mg/l) |                                  |
| Cadmium (T) .....               | 0.11                        | 0.07                             |
| Chromium (T) .....              | 2.77                        | 1.71                             |
| Copper (T) .....                | 3.38                        | 2.07                             |
| Lead (T) .....                  | 0.69                        | 0.43                             |
| Nickel (T) .....                | 3.98                        | 2.38                             |
| Silver (T) .....                | 0.43                        | 0.24                             |
| Zinc (T) .....                  | 2.61                        | 1.48                             |
| Cyanide (T) .....               | 1.20                        | 0.65                             |
| TTO .....                       | 2.13                        | .....                            |

(b) Alternatively, for industrial facilities with cyanide treatment, and upon agreement between a source subject to these limits and the pollution control authority, the following amenable cyanide limit may apply in place of the total cyanide limit specified in paragraph (a) of this section:

| Pollutant or pollutant property | Maximum for any 1 day       | Monthly average shall not exceed |
|---------------------------------|-----------------------------|----------------------------------|
|                                 | Milligrams per liter (mg/l) |                                  |
| Cyanide (A) .....               | 0.86                        | 0.32                             |

(c) No user subject to the provisions of this subpart shall augment the use

of process wastewater or otherwise dilute the wastewater as a partial or total substitute for adequate treatment to achieve compliance with this limitation.

(d) An existing source submitting a certification in lieu of monitoring pursuant to §433.12 (a) and (b) of this regulation must implement the toxic organic management plan approved by the control authority.

[48 FR 32485, July 15, 1983; 48 FR 43682, Sept. 26, 1983]

**PART 434—COAL MINING POINT SOURCE CATEGORY BPT, BAT, BCT LIMITATIONS AND NEW SOURCE PERFORMANCE STANDARDS**

**Subpart A—General Provisions**

Sec.

434.10 Applicability.

434.11 General definitions.

**Subpart B—Coal Preparation Plants and Coal Preparation Plant Associated Areas**

434.20 Applicability.

434.21 [Reserved]

434.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

434.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

434.24 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

434.25 New source performance standard (NSPS).

**Subpart C—Acid or Ferruginous Mine Drainage**

434.30 Applicability; description of the acid or ferruginous mine drainage subcategory.

434.31 [Reserved]

434.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

434.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best

available technology economically achievable (BAT).

434.34 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

434.35 New source performance standards (NSPS).

**Subpart D—Alkaline Mine Drainage**

434.40 Applicability; description of the alkaline mine drainage subcategory

434.41 [Reserved]

434.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

434.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

434.44 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

434.45 New source performance standards (NSPS).

**Subpart E—Post-Mining Areas**

434.50 Applicability.

434.51 [Reserved]

434.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

434.53 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

434.54 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

434.55 New source performance standards (NSPS).

**Subpart F—Miscellaneous Provisions**

434.60 Applicability.

434.61 Commingling of waste streams.

434.62 Alternate effluent limitations for pH.

434.63 Effluent limitations for precipitation events.

434.64 Procedure and method detection limit for measurement of settleable solids.

434.65 Modifications of NPDES Permits for New Sources.