

BAT EFFLUENT LIMITATIONS—Continued

Stream	Pollutant parameter	BAT effluent limitations
(A) All coastal areas except Cook Inlet	No discharge.
(B) Cook Inlet	Oil & Grease	The maximum for any one day shall not exceed 42 mg/l, and the 30-day average shall not exceed 29 mg/l.
Produced Sand	No discharge.
Deck Drainage	Free Oil ³	No discharge.
Domestic Waste	Foam	No discharge.

¹ BAT limitations for dewatering effluent are applicable prospectively. BAT limitations in this rule are not applicable to discharges of dewatering effluent from reserve pits which as of the effective date of this rule no longer receive drilling fluids and drill cuttings. Limitations on such discharges shall be determined by the NPDES permit issuing authority.

² As determined by the static sheen test (see appendix 1 to 40 CFR Part 435, subpart A).

³ As determined by the presence of a film or sheen upon or a discoloration of the surface of the receiving water (visual sheen).

⁴ As determined by the toxicity test (see appendix 2 of 40 CFR Part 435, subpart A).

[61 FR 66125, Dec. 16, 1996; 62 FR 1681, Jan. 13, 1997]

§ 435.44 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30-125.32, any existing point source sub-

ject to this Subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT):

BCT EFFLUENT LIMITATIONS

Stream	Pollutant parameter	BCT effluent limitations
Produced Water (all facilities)	Oil & Grease	The maximum for any one day shall not exceed 72 mg/l and the 30-day average shall not exceed 48 mg/l.
Drilling Fluids and Drill Cuttings and Dewatering Effluent: ¹		
All facilities except Cook Inlet	No discharge.
Cook Inlet	Free Oil	No discharge. ²
Well Treatment, Workover and Completion Fluids.	Free Oil	No discharge. ²
Produced Sand	No discharge.
Deck Drainage	Free Oil	No discharge. ³
Sanitary Waste:		
Sanitary M10	Residual Chlorine	Minimum of 1 mg/l maintained as close to this concentration as possible.
Sanitary M91M	Floating Solids	No discharge.
Domestic Waste	Floating Solids and garbage	No discharge of Floating Solids or garbage.

¹ BCT limitations for dewatering effluent are applicable prospectively. BCT limitations in this rule are not applicable to discharges of dewatering effluent from reserve pits which as of the effective date of this rule no longer receive drilling fluids and drill cuttings. Limitations on such discharges shall be determined by the NPDES permit issuing authority.

² As determined by the static sheen test (see appendix 1 to 40 CFR part 435, subpart A).

³ As determined by the presence of a film or sheen upon or a discoloration of the surface of the receiving water (visual sheen).

[61 FR 66125, Dec. 16, 1996; 62 FR 1682, Jan. 13, 1997]

§ 435.45 Standards of performance for new sources (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

NSPS EFFLUENT LIMITATIONS

Stream	Pollutant parameter	NSPS effluent limitations
Produced Water:		
(A) All coastal areas except Cook Inlet	No discharge.