

PART 443—EFFLUENT LIMITATIONS GUIDELINES FOR EXISTING SOURCES AND STANDARDS OF PERFORMANCE AND PRETREATMENT STANDARDS FOR NEW SOURCES FOR THE PAVING AND ROOFING MATERIALS (TARS AND ASPHALT) POINT SOURCE CATEGORY

Subpart A—Asphalt Emulsion Subcategory

Sec.

- 443.10 Applicability; description of the asphalt emulsion subcategory.
- 443.11 Specialized definitions.
- 443.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 443.14 [Reserved]
- 443.15 Standards of performance for new sources.
- 443.16 Pretreatment standards for new sources.

Subpart B—Asphalt Concrete Subcategory

- 443.20 Applicability; description of the asphalt concrete subcategory.
- 443.21 Specialized definitions.
- 443.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 443.24 [Reserved]
- 443.25 Standards of performance for new sources.
- 443.26 Pretreatment standard for new sources.

Subpart C—Asphalt Roofing Subcategory

- 443.30 Applicability; description of the asphalt roofing subcategory.
- 443.31 Specialized definitions.
- 443.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.33 Effluent limitations guidelines representing the degree of effluent reduction

attainable by the application of the best available technology economically achievable.

- 443.34 [Reserved]
- 443.35 Standards of performance for new sources.
- 443.36 Pretreatment standard for new sources.

Subpart D—Linoleum and Printed Asphalt Felt Subcategory

- 443.40 Applicability; description of the linoleum and printed asphalt felt subcategory.
- 443.41 Specialized definitions.
- 443.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 443.44 [Reserved]
- 443.45 Standards of performance for new sources.
- 443.46 Pretreatment standards for new sources.

AUTHORITY: Secs. 301, 304 (b) and (c), 306 (b) and (c) and 307(c), Federal Water Pollution Control Act, as amended (the Act); 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), 1317(c), 86 Stat. 816 *et seq.*; Pub. L. 92–500.

SOURCE: 40 FR 31191, July 24, 1975, unless otherwise noted.

Subpart A—Asphalt Emulsion Subcategory

§ 443.10 Applicability; description of the asphalt emulsion subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of asphalt paving and roofing emulsions.

§ 443.11 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term “production area size” shall mean that area in which the oxidation towers, loading facilities, and all buildings that house product processes are located.