

§ 465.42

40 CFR Ch. I (7-1-00 Edition)

SUBPART D—BPT EFFLUENT LIMITATIONS

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly average |
|-------------------------------------|-----------------------|-----------------------------|
| g (lbs)/1,000,000 cans manufactured | | |
| Cr | 94.60 (0.209) | 38.70 (0.085) |
| Zn | 313.90 (0.692) | 131.15 (0.289) |
| Al | 1382.45 (3.048) | 688.00 (1.517) |
| F | 12792.50 (28.203) | 5676.00 (12.514) |
| P | 3590.50 (7.916) | 1468.45 (3.237) |
| O & G | 4300.00 (9.480) | 2580.00 (5.688) |
| TSS | 8815.00 (19.434) | 4192.50 (9.243) |
| pH | (¹) | (¹) |

¹Within the range of 7.0 to 10 at all times.

[48 FR 52399, Nov. 17, 1983; 49 FR 14105, Apr. 10, 1984]

§ 465.42 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

SUBPART D—BAT EFFLUENT LIMITATIONS

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly average |
|-------------------------------------|-----------------------|-----------------------------|
| g (lbs)/1,000,000 cans manufactured | | |
| Cr | 36.92 (0.081) | 15.10 (0.033) |
| Zn | 122.49 (0.270) | 51.18 (0.113) |
| Al | 539.48 (1.189) | 268.48 (0.592) |
| F | 4992.05 (11.001) | 2214.96 (4.883) |
| P | 1401.13 (3.089) | 573.04 (1.263) |

SUBPART D—PSES

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly average |
|--------------------------------------|-----------------------|-----------------------------|
| Cr | 36.92 (0.081) | 15.10 (0.033) |
| Cu | 159.41 (0.351) | 83.90 (0.185) |
| Zn | 122.49 (0.270) | 51.18 (0.113) |
| F | 4992.05 (11.001) | 2214.96 (4.883) |
| P | 1401.13 (3.089) | 573.04 (1.263) |
| Mn | 57.05 (0.126) | 24.33 (0.053) |
| TTO | 26.85 (0.059) | 12.59 (0.028) |
| O&G (for alternate monitoring) | 1678.00 (3.699) | 1006.80 (2.220) |

§ 465.43 New source performance standards.

The following standards of performance establish the quantity of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

SUBPART D—NSPS

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly average |
|-------------------------------------|-----------------------|-----------------------------|
| g (lbs)/1,000,000 cans manufactured | | |
| Cr | 27.98 (0.062) | 11.45 (0.025) |
| Zn | 92.86 (0.205) | 38.80 (0.086) |
| Al | 408.95 (0.902) | 203.52 (0.449) |
| F | 3784.20 (8.343) | 1679.04 (3.702) |
| P | 1062.12 (2.342) | 434.39 (0.958) |
| O & G | 1272.00 (2.804) | 763.20 (1.683) |
| TSS | 2607.60 (5.749) | 1240.20 (2.734) |
| pH | (¹) | (¹) |

¹Within the range of 7.0 to 10 at all times.

[48 FR 52399, Nov. 17, 1983; 49 FR 14105, Apr. 10, 1984]

§ 465.44 Pretreatment standards for existing sources.

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources.

Environmental Protection Agency

Pt. 466

[48 FR 52399, Nov. 17, 1983; 49 FR 14105, Apr. 10, 1984]

§ 465.45 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7 any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources.

SUBPART D—PSNS

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly average |
|--------------------------------------|-------------------------------------|-----------------------------|
| | g (lbs)/1,000,000 cans manufactured | |
| Cr | 27.98 (0.0617) | 11.45 (0.025) |
| Cu | 120.84 (0.267) | 63.60 (0.140) |
| Zn | 92.86 (0.205) | 38.80 (0.086) |
| F | 3784.20 (8.345) | 1679.04 (3.702) |
| P | 1062.12 (2.342) | 434.39 (0.958) |
| Mn | 43.25 (0.095) | 18.44 (0.041) |
| TTO | 20.35 (0.045) | 9.54 (0.0210) |
| O&G (for alternate monitoring) | 1272.00 (2.804) | 763.20 (1.683) |

[48 FR 52399, Nov. 17, 1983; 49 FR 14105, Apr. 10, 1984]

§ 465.46 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

PART 466—PORCELAIN ENAMELING POINT SOURCE CATEGORY

GENERAL PROVISIONS

- Sec.
- 466.01 Applicability.
- 466.02 General definitions.
- 466.03 Monitoring and reporting requirements.
- 466.04 Compliance date for PSES.

Subpart A—Steel Basis Material Subcategory

- 466.10 Applicability; description of the steel basis material.
- 466.11 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 466.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 466.13 New source performance standards.

- 466.14 Pretreatment standards for existing sources.
- 466.15 Pretreatment standards for new sources.

Subpart B—Cast Iron Basis Material Subcategory

- 466.20 Applicability; description of the cast iron basis material subcategory.
- 466.21 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 466.22 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 466.23 New source performance standards.
- 466.24 Pretreatment standards for existing sources.
- 466.25 Pretreatment standards for new sources.

Subpart C—Aluminum Basis Material Subcategory

- 466.30 Applicability; description of the aluminum basis material subcategory.
- 466.31 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 466.32 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 466.33 New source performance standards.
- 466.34 Pretreatment standards for existing sources.
- 466.35 Pretreatment standards for new sources.

Subpart D—Copper Basis Material Subcategory

- 466.40 Applicability; description of the copper basis material subcategory.
- 466.41—466.42 [Reserved]
- 466.43 New source performance standards.
- 466.44 [Reserved]
- 466.45 Pretreatment standards for new sources.

AUTHORITY: Secs. 301, 304 (b), (c), (e), and (g), 306 (b) and (c), 307 and 501 of the Clean Water Act (the Federal Water Pollution Control Act Amendments of 1972, as amended by the Clean Water Act of 1977) (the "Act"); 33 U.S.C. 1311, 1314 (b), (c), (e) and (g), 1316 (b) and (c), 1317 (b) and (c), and 1361; 86 Stat. 816, Pub. L. 92-500; 91 Stat. 1567, Pub. L. 95-217.

SOURCE: 47 FR 53184, Nov. 24, 1982, unless otherwise noted.