

**§ 60.270a**

**40 CFR Ch. I (7-1-00 Edition)**

postmarked 30 days prior to the performance test.

(c) For the purpose of this subpart, the owner or operator shall conduct the demonstration of compliance with § 60.272(a) of this subpart and furnish the Administrator a written report of the results of the test. This report shall include the following information:

- (1) Facility name and address;
  - (2) Plant representative;
  - (3) Make and model of process, control device, and continuous monitoring equipment;
  - (4) Flow diagram of process and emission capture equipment including other equipment or process(es) ducted to the same control device;
  - (5) Rated (design) capacity of process equipment;
  - (6) Those data required under § 60.274(i) of this subpart:
    - (i) List of charge and tap weights and materials;
    - (ii) Heat times and process log;
    - (iii) Control device operation log; and
    - (iv) Continuous monitor or Reference Method 9 data.
  - (7) Test dates and test times;
  - (8) Test company;
  - (9) Test company representative;
  - (10) Test observers from outside agency;
  - (11) Description of test methodology used, including any deviation from standard reference methods
  - (12) Schematic of sampling location;
  - (13) Number of sampling points;
  - (14) Description of sampling equipment;
  - (15) Listing of sampling equipment calibrations and procedures;
  - (16) Field and laboratory data sheets;
  - (17) Description of sample recovery procedures;
  - (18) Sampling equipment leak check results;
  - (19) Description of quality assurance procedures;
  - (20) Description of analytical procedures;
  - (21) Notation of sample blank corrections; and
  - (22) Sample emission calculations.
- (d) The owner or operator shall maintain records of all shop opacity observations made in accordance with § 60.273(d). All shop opacity observa-

tions in excess of the emission limit specified in § 60.272(a)(3) of this subpart shall indicate a period of excess emission, and shall be reported to the Administrator semi-annually, according to § 60.7(c).

[49 FR 43844, Oct. 31, 1984, as amended at 54 FR 6672, Feb. 14, 1989; 64 FR 10110, Mar. 2, 1999]

**Subpart AAa—Standards of Performance for Steel Plants: Electric Arc Furnaces and Argon-Oxygen Decarburization Vessels Constructed After August 17, 1983**

SOURCE: 49 FR 43845, Oct. 31, 1984, unless otherwise noted.

**§ 60.270a Applicability and designation of affected facility.**

(a) The provisions of this subpart are applicable to the following affected facilities in steel plants that produce carbon, alloy, or specialty steels: electric arc furnaces, argon-oxygen decarburization vessels, and dust-handling systems.

(b) The provisions of this subpart apply to each affected facility identified in paragraph (a) of this section that commences construction, modification, or reconstruction after August 17, 1983.

**§ 60.271a Definitions.**

As used in this subpart, all terms not defined herein shall have the meaning given them in the Act and in subpart A of this part.

*Argon-oxygen decarburization vessel* (AOD vessel) means any closed-bottom, refractory-lined converter vessel with submerged tuyeres through which gaseous mixtures containing argon and oxygen or nitrogen may be blown into molten steel for further refining.

*Capture system* means the equipment (including ducts, hoods, fans, dampers, etc.) used to capture or transport particulate matter generated by an electric arc furnace or AOD vessel to the air pollution control device.

*Charge* means the addition of iron and steel scrap or other materials into the top of an electric arc furnace or the