

Environmental Protection Agency

§ 60.493

G=the volume-weighted average of VOC in coatings consumed in a calendar month per volume of coating solids applied (kilograms per litre of coating solids)
H_c=the fraction of VOC emitted at the coater and flashoff areas captured by a collection system
H_h=the fraction of VOC emitted at the cure oven captured by a collection system
L_c=the volume of each coating consumed, as received (litres)
L_d=the volume of each VOC-solvent added to coatings (litres)
L_r=the volume of VOC-solvent recovered by an emission control device (litres)
L_s=the volume of coating solids consumed (litres)
M_d=the mass of VOC-solvent added to coatings (kilograms)
M_o=the mass of VOC-solvent in coatings consumed, as received (kilograms)
M_r=the mass of VOC-solvent recovered by emission control device (kilograms)
N=the volume-weighted average mass of VOC emissions to atmosphere per unit volume of coating solids applied (kilograms per litre of coating solids)
Q_a=the volumetric flow rate of each gas stream leaving the control device and entering the atmosphere (dry standard cubic meters per hour)
Q_b=the volumetric flow of each gas stream entering the control device (dry standard cubic meters per hour)
R=the overall emission reduction efficiency for an affected facility (fraction)
S_e=the fraction of VOC in coating and diluent VOC-solvent emitted at the coater and flashoff area for a coating operation
S_h=the fraction of VOC in coating and diluent solvent emitted at the cure oven for a coating operation
V_s=the proportion of solids in each coating, as received (fraction by volume)
W_o=the proportion of VOC in each coating, as received (fraction by weight).

§ 60.492 Standards for volatile organic compounds.

On or after the date on which the initial performance test required by § 60.8(a) is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge of VOC emissions to the atmosphere that exceed the following volume-weighted calendar-month average emissions:

(a) 0.29 kilogram of VOC per litre of coating solids from each two-piece can exterior base coating operation, except clear base coat;

(b) 0.46 kilogram of VOC per litre of coating solids from each two-piece can clear base coating operation and from

each overvarnish coating operation; and

(c) 0.89 kilogram of VOC per litre of coating solids from each two-piece can inside spray coating operation.

§ 60.493 Performance test and compliance provisions.

(a) Section 60.8(d) does not apply to monthly performance tests and § 60.8(f) does not apply to the performance test procedures required by this subpart.

(b) The owner or operator of an affected facility shall conduct an initial performance test as required under § 60.8(a) and thereafter a performance test each calendar month for each affected facility.

(1) The owner or operator shall use the following procedures for each affected facility that does not use a capture system and a control device to comply with the emission limit specified under § 60.492. The owner or operator shall determine the VOC-content of the coatings from formulation data supplied by the manufacturer of the coating or by an analysis of each coating, as received, using Reference Method 24. The Administrator may require the owner or operator who uses formulation data supplied by the manufacturer of the coating to determine the VOC content of coatings using Reference Method 24 or an equivalent or alternative method. The owner or operator shall determine from company records the volume of coating and the mass of VOC-solvent added to coatings. If a common coating distribution system serves more than one affected facility or serves both affected and existing facilities, the owner or operator shall estimate the volume of coating used at each facility by using the average dry weight of coating, number of cans, and size of cans being processed by each affected and existing facility or by other procedures acceptable to the Administrator.

(i) Calculate the volume-weighted average of the total mass of VOC per volume of coating solids used during the calendar month for each affected facility, except as provided under paragraph (b)(1)(iv) of this section. The volume-weighted average of the total mass of VOC per volume of coating solids used