

## Environmental Protection Agency

## § 60.493

coating operation consists of the coating application station, flashoff area, and curing oven.

(5) *Two-piece can* means any beverage can that consists of a body manufactured from a single piece of steel or aluminum and a top. Coatings for a two-piece can are usually applied after fabrication of the can body.

(6) *VOC content* means all volatile organic compounds (VOC) that are in a coating. VOC content is expressed in terms of kilograms of VOC per litre of coating solids.

(b) Notations used under §60.493 of this subpart are defined below:

$C_a$ =the VOC concentration in each gas stream leaving the control device and entering the atmosphere (parts per million as carbon)

$C_b$ =the VOC concentration in each gas stream entering the control device (parts per million as carbon)

$D_c$ =density of each coating, as received (kilograms per litre)

$D_d$ =density of each VOC-solvent added to coatings (kilograms per litre)

$D_r$ =density of VOC-solvent recovered by an emission control device (kilograms per litre)

$E$ =VOC destruction efficiency of the control device (fraction)

$F$ =the proportion of total VOC emitted by an affected facility which enters the control device to total emissions (fraction)

$G$ =the volume-weighted average of VOC in coatings consumed in a calendar month per volume of coating solids applied (kilograms per litre of coating solids)

$H_c$ =the fraction of VOC emitted at the coater and flashoff areas captured by a collection system

$H_h$ =the fraction of VOC emitted at the cure oven captured by a collection system

$L_c$ =the volume of each coating consumed, as received (litres)

$L_d$ =the volume of each VOC-solvent added to coatings (litres)

$L_r$ =the volume of VOC-solvent recovered by an emission control device (litres)

$L_s$ =the volume of coating solids consumed (litres)

$M_d$ =the mass of VOC-solvent added to coatings (kilograms)

$M_o$ =the mass of VOC-solvent in coatings consumed, as received (kilograms)

$M_r$ =the mass of VOC-solvent recovered by emission control device (kilograms)

$N$ =the volume-weighted average mass of VOC emissions to atmosphere per unit volume of coating solids applied (kilograms per litre of coating solids)

$Q_a$ =the volumetric flow rate of each gas stream leaving the control device and en-

tering the atmosphere (dry standard cubic meters per hour)

$Q_b$ =the volumetric flow of each gas stream entering the control device (dry standard cubic meters per hour)

$R$ =the overall emission reduction efficiency for an affected facility (fraction)

$S_c$ =the fraction of VOC in coating and diluent VOC-solvent emitted at the coater and flashoff area for a coating operation

$S_h$ =the fraction of VOC in coating and diluent solvent emitted at the cure oven for a coating operation

$V_s$ =the proportion of solids in each coating, as received (fraction by volume)

$W_o$ =the proportion of VOC in each coating, as received (fraction by weight).

### § 60.492 Standards for volatile organic compounds.

On or after the date on which the initial performance test required by §60.8(a) is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge of VOC emissions to the atmosphere that exceed the following volume-weighted calendar-month average emissions:

(a) 0.29 kilogram of VOC per litre of coating solids from each two-piece can exterior base coating operation, except clear base coat;

(b) 0.46 kilogram of VOC per litre of coating solids from each two-piece can clear base coating operation and from each overvarnish coating operation; and

(c) 0.89 kilogram of VOC per litre of coating solids from each two-piece can inside spray coating operation.

### § 60.493 Performance test and compliance provisions.

(a) Section 60.8(d) does not apply to monthly performance tests and §60.8(f) does not apply to the performance test procedures required by this subpart.

(b) The owner or operator of an affected facility shall conduct an initial performance test as required under §60.8(a) and thereafter a performance test each calendar month for each affected facility.

(1) The owner or operator shall use the following procedures for each affected facility that does not use a capture system and a control device to comply with the emission limit specified under §60.492. The owner or operator shall determine the VOC-content