

Environmental Protection Agency

§ 761.65

or storage activities under this paragraph prior to obtaining written approval by EPA.

(2) EPA will issue a written decision on each application for a risk-based sampling, disposal, or storage method for PCB bulk product wastes. EPA will approve such an application if it finds that the method will not pose an unreasonable risk of injury to health or the environment.

(d) *Disposal as daily landfill cover or roadbed.* Bulk product waste described in paragraph (b)(1) of this section may be disposed of:

(1) As daily landfill cover as long as the daily cover remains in the landfill and is not released or dispersed by wind or other action; or

(2) Under asphalt as part of a road bed.

[63 FR 35451, June 29, 1998, as amended at 64 FR 33761, June 24, 1999]

§ 761.63 PCB household waste storage and disposal.

PCB household waste, as defined at § 761.3, managed in a facility permitted, licensed, or registered by a State to manage municipal or industrial solid waste, or in a facility with an approval to dispose of PCB bulk product waste under § 761.62(c), is not subject to any other requirements of part 761 of this chapter. PCB household waste stored in a unit regulated for storage of PCB waste must not be commingled with PCB waste.

[63 FR 35452, June 29, 1998]

§ 761.64 Disposal of wastes generated as a result of research and development activities authorized under § 761.30(j) and chemical analysis of PCBs.

This section provides disposal requirements for wastes generated during and as a result of research and development authorized under § 761.30(j). This section also provides disposal requirements for wastes generated during the chemical analysis of samples containing PCBs under part 761, including §§ 761.30, 761.60, 761.61, 761.62, and 761.79. For determining the presence of PCBs in samples, chemical analysis includes: sample preparation, sample extraction, extract cleanup, extract concentration,

addition of PCB standards, and instrumental analysis.

(a) Portions of samples of a size designated in a chemical extraction and analysis method for PCBs and extracted for purposes of determining the presence of PCBs or concentration of PCBs are unregulated for PCB disposal under this part.

(b) All other wastes generated during these activities are regulated for disposal based on their concentration at the time of disposal as follows:

(1) Liquid wastes, including rinse solvents, must be disposed of according to § 761.61(a)(5)(iv).

(2) Non-liquid wastes must be disposed of in the same manner as non-liquid cleaning materials and personal protective equipment waste according to § 761.61(a)(5)(v)(A).

[63 FR 35452, June 29, 1998]

§ 761.65 Storage for disposal.

This section applies to the storage for disposal of PCBs at concentrations of 50 ppm or greater and PCB Items with PCB concentrations of 50 ppm or greater.

(a)(1) *Storage limitations.* Any PCB waste shall be disposed of as required by subpart D of this part within 1-year from the date it was determined to be PCB waste and the decision was made to dispose of it. This date is the date of removal from service for disposal and the point at which the 1-year time frame for disposal begins. PCB/radioactive waste removed from service for disposal is exempt from the 1-year time limit provided that the provisions at paragraphs (a)(2)(ii) and (a)(2)(iii) of this section are followed and the waste is managed in accordance with all other applicable Federal, State, and local laws and regulations for the management of radioactive material.

(2) *One-year extension.* Any person storing PCB waste that is subject to the 1-year time limit for storage and disposal in paragraph (a)(1) of this section may provide written notification to the EPA Regional Administrator for the Region in which the PCB waste is stored that their continuing attempts to dispose of or secure disposal for their waste within the 1-year time