

§ 108.520 Type of survival craft.

(a) Each lifeboat must be a fire-protected lifeboat approved under approval series 160.035. A lifeboat of aluminum construction in the hull or canopy must be protected in its stowage position by a water spray system meeting the requirements of part 34, subpart 34.25 of this chapter.

(b) Each inflatable liferaft must be approved under approval series 160.151. Each rigid liferaft must be approved under approval series 160.118. Each liferaft must have a capacity of six persons or more.

[CGD 84-069, 61 FR 25291, May 20, 1996, as amended by USCG-2006-25697, 71 FR 55746, Sept. 25, 2006]

§ 108.525 Survival craft number and arrangement.

(a) Each unit must carry the following:

(1) Lifeboats installed in at least two widely separated locations on different sides or ends of the unit. The arrangement of the lifeboats must provide sufficient capacity to accommodate the total number of persons permitted on board if—

(i) All the lifeboats in any one location are lost or rendered unusable; or

(ii) All the lifeboats on any one side or end of the unit are lost or rendered unusable.

(2) Liferafts arranged for float-free launching and having an aggregate capacity that will accommodate the total number of persons permitted on board.

(b) In the case of a self-elevating unit where, due to its size or configuration, lifeboats can not be located in the widely separated locations required under paragraph (a)(1) of this section, the OCMI may accept the following number and arrangement of survival craft:

(1) Lifeboats with an aggregate capacity to accommodate the total number of persons permitted on board.

(2) Liferafts served by launching appliances or marine evacuation systems of an aggregate capacity to accommodate the total number of persons permitted on board. These liferafts may be the float-free liferafts under paragraph (a)(2) of this section, or liferafts in addition to the float-free liferafts.

§ 108.530 Stowage of survival craft.

(a) *General.* Each survival craft required to be served by a launching appliance or marine evacuation system must be stowed as follows:

(1) Each survival craft must be stowed as close to the accommodation and service spaces as possible.

(2) Each survival craft must be stowed in a way that neither the survival craft nor its stowage arrangements will interfere with the embarkation and operation of any other survival craft or rescue boat at any other launching station.

(3) Each survival craft must be stowed as near the water surface as is safe and practicable.

(4) Each survival craft must be stowed where the survival craft, in the embarkation position, is above the waterline with the unit—

(i) In the fully loaded condition; and

(ii) Listed up to 20 degrees either way, or to the angle where the unit's weatherdeck edge becomes submerged, whichever is less.

(5) Each survival craft must be sufficiently ready for use so that two crew members can complete preparations for embarkation and launching in less than 5 minutes.

(6) Each survival craft must be fully equipped as required under this subpart.

(7) Each survival craft must be in a secure and sheltered position and protected from damage by fire and explosion, as far as practicable.

(8) Each survival craft must not require lifting from its stowed position in order to launch, except that a davit-launched liferaft may be lifted by a manually powered winch from its stowed position to its embarkation position.

(b) *Additional lifeboat-specific stowage requirements.* In addition to meeting the requirements of paragraph (a) of this section, each lifeboat must be stowed as follows:

(1) The unit must be arranged so each lifeboat, in its stowed position, is protected from damage by heavy seas.

(2) Each lifeboat must be stowed attached to its launching appliance.