

## Coast Guard, DHS

## § 108.719

(b) The self-contained breathing apparatus required in § 108.497 may be used for this purpose.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by CGD 86-036, 57 FR 48326, Oct. 23, 1992]

### § 108.705 Anchors, chains, wire rope, and hawsers.

(a) Each unit must be fitted with anchors, chains, wire rope, and hawsers in agreement with the standards established by the American Bureau of Shipping.

(b) Units which are equipped with anchors used as operational equipment are not required to have additional anchors if the operational anchors meet the requirements of paragraph (a) of this section.

[CGD 73-251, 43 FR 56808, Dec. 4, 1978, as amended by USCG-1999-6216, 64 FR 53226, Oct. 1, 1999]

### § 108.707 First aid kit.

Each unit must have a first-aid kit approved by the Mine Safety and Health Administration (Formerly Mining Enforcement and Safety Administration) of a size suitable for the number of persons allowed on board the unit that is stowed in a location that is accessible to persons on board.

### § 108.709 Litter.

Each unit must have a litter that is—

(a) Stowed in a location that is accessible to the persons on board; and

(b) Capable of being used on the type of helicopters serving the unit.

### § 108.713 International Code of Signals.

Each vessel on an international voyage which is required to carry a radiotelegraph or radiotelephone installation in accordance with Chapter IV of the Safety of Life at Sea Convention, 1960, must carry the International Code of Signals.

### § 108.715 Magnetic compass and gyrocompass.

(a) Each self-propelled unit in ocean or coastwise service must have a magnetic compass.

(b) Each self-propelled unit of 1,600 gross tons and over in ocean or coastwise service must have a gyrocompass

in addition to the magnetic compass required in paragraph (a) of this section.

(c) Each unit that is required to have a gyrocompass must have an illuminated repeater for the gyrocompass that is at the main steering stand unless the gyrocompass is illuminated and is at the main steering stand.

### § 108.717 Radar.

Each self-propelled unit of 1,600 gross tons and over in ocean or coastwise service must have—

(a) A marine radar system for surface navigation; and

(b) Facilities on the bridge for plotting radar readings.

### § 108.719 Pilot boarding equipment.

(a) This section applies to each vessel that normally embarks or disembarks a pilot from a pilot boat or other vessel.

(b) Each vessel must have suitable pilot boarding equipment available for use on each side of the vessel. If a vessel has only one set of equipment, the equipment must be capable of being easily transferred to and rigged for use on either side of the vessel.

(c) Pilot boarding equipment must be capable of resting firmly against the vessel's side and be secured so that it is clear from overboard discharges.

(d) Each vessel must have lighting positioned to provide adequate illumination for the pilot boarding equipment and each point of access.

(e) Each vessel must have a point of access that has—

(1) A gateway in the rails or bulwark with adequate handholds; or

(2) Two handhold stanchions and a bulwark ladder that is securely attached to the bulwark rail and deck.

(f) The pilot boarding equipment required by paragraph (b) of this section must include at least one pilot ladder approved under subpart 163.003 of this chapter. Each pilot ladder must be of a single length and capable of extending from the point of access to the water's edge during each condition of loading and trim, with an adverse list of 15°.

(g) Whenever the distance from the water's edge to the point of access is more than 30 feet, access from a pilot ladder to the vessel must be by way of