

§ 108.801

an accommodation ladder or equally safe and convenient means.

(h) Pilot hoists, if used, must be approved under subpart 163.002 of this chapter.

[CGD 79-032, 49 FR 25455, June 21, 1984]

Subpart I—Navigation Bridge Visibility

§ 108.801 Navigation bridge visibility.

Each mobile offshore drilling unit which is 100 meters (328 feet) or more in length and contracted for on or after September 7, 1990, must meet the following requirements:

(a) The field of vision from the navigation bridge, whether the vessel is in a laden or unladen condition, must be such that:

(1) From the conning position, the view of the sea surface is not obscured forward of the bow by more than the lesser of two ship lengths or 500 meters (1,640 feet) from dead ahead to 10 degrees on either side of the vessel. Within this arc of visibility any blind sector caused by cargo, cargo gear, or other permanent obstruction must not exceed 5 degrees.

(2) From the conning position, the horizontal field of vision extends over an arc from at least 22.5 degrees abaft the beam on one side of the vessel, through dead ahead, to at least 22.5 degrees abaft the beam on the other side of the vessel. Blind sectors forward of the beam caused by cargo, cargo gear, or other permanent obstruction must not exceed 10 degrees each, nor total more than 20 degrees, including any blind sector within the arc of visibility described in paragraph (a)(1) of this section.

(3) From each bridge wing, the field of vision extends over an arc from at least 45 degrees on the opposite bow, through dead ahead, to at least dead astern.

(4) From the main steering position, the field of vision extends over an arc from dead ahead to at least 60 degrees on either side of the vessel.

(5) From each bridge wing, the respective side of the vessel is visible forward and aft.

(b) Windows fitted on the navigation bridge must be arranged so that:

46 CFR Ch. I (10-1-22 Edition)

(1) Framing between windows is kept to a minimum and is not installed immediately in front of any work station.

(2) Front windows are inclined from the vertical plane, top out, at an angle of not less than 10 degrees and not more than 25 degrees.

(3) The height of the lower edge of the front windows is limited to prevent any obstruction of the forward view previously described in this section.

(4) The height of the upper edge of the front windows allows a forward view of the horizon at the conning position, for a person with a height of eye of 1.8 meters (71 inches), when the vessel is at a forward pitch angle of 20 degrees.

(c) Polarized or tinted windows must not be fitted.

[CGD 85-099, 55 FR 32248, Aug. 8, 1990]

Subpart J—Muster List

§ 108.901 Muster list and emergency instructions.

(a) *General.* Copies of clear instructions must be provided on the unit, detailing the actions that each person on board should follow in the event of an emergency.

(b) *Muster list.* Copies of the muster list must be posted in conspicuous places throughout the unit including on the navigating bridge, in the control room, and in accommodation spaces. The muster list must be posted at all times while the unit is in service. After the muster list has been prepared, if any change takes place that necessitates an alteration in the muster list, the person in charge must either revise the muster list or prepare a new one. Muster lists must provide the following information:

(1) Each muster list must specify instructions for operating the general emergency alarm system.

(2) Each muster list must specify the emergency signals.

(3) Each muster list must specify the actions to be taken by the crew and industrial personnel when each signal is sounded.

(4) Each muster list must specify how the order to abandon the unit will be given.

(5) Each muster list must specify the persons that are assigned to make sure

that lifesaving and firefighting appliances are maintained in good condition and ready for immediate use.

(6) The muster list must specify the duties assigned to the different industrial personnel and members of the crew that include—

(i) Closing the watertight doors, fire doors, valves, scuppers, sidescuttles, skylights, portholes, and other similar openings in the unit's hull;

(ii) Equipping the survival craft and other lifesaving appliances;

(iii) Preparing and launching the survival craft;

(iv) Preparing other lifesaving appliances;

(v) Mustering the visitors and other persons in addition to the crew and industrial personnel;

(vi) Using communication equipment;

(vii) Manning the emergency squad assigned to deal with fires and other emergencies;

(viii) Special duties assigned with respect to the use of firefighting equipment and installations;

(ix) Cover the duties of the crew and industrial personnel in case of collisions or other serious casualties; and

(x) Cover the duties of the crew and industrial personnel in case of severe storms.

(7) Each muster list must specify the duties assigned to industrial personnel and members of the crew in relation to visitors and other persons on board in case of an emergency that include—

(i) Warning visitors and other persons on board;

(ii) Seeing that visitors and other persons on board are suitably dressed and have donned their lifejackets or immersion suits correctly;

(iii) Assembling visitors and other persons on board at muster stations; and

(iv) Keeping order in the passageways and on the stairways and generally controlling the movements of the visitors and other persons on board;

(8) Each muster list must specify substitutes for key persons if they are disabled, taking into account that different emergencies require different actions.

(c) *Emergency instructions.* Illustrations and instructions in English and

any other appropriate language, as determined by the OCMI, must be posted in each cabin used for persons who are not members of the crew or industrial personnel. They must be conspicuously displayed at each muster station and in other accommodation spaces to inform personnel of—

(1) The fire and emergency signal;

(2) Their muster station;

(3) The essential actions they must take in an emergency;

(4) The location of lifejackets, including child-size lifejackets;

(5) The method of donning lifejackets;

(6) If immersion suits are provided, the location of the immersion suits; and

(7) Fully illustrated instructions on the method of donning immersion suits.

[CGD 84-069, 61 FR 25299, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

PART 109—OPERATIONS

Subpart A—General

Sec.

109.101 Applicability.

109.103 Requirements of the International Convention for Safety of Life at Sea, 1974.

109.105 Incorporation by reference.

109.107 Designation of master or person in charge.

109.109 Responsibilities of master or person in charge.

109.121 Operating manual.

Subpart B—Tests, Drills, and Inspections

109.201 Steering gear, whistles, general alarm, and means of communication.

109.203 Sanitation.

109.205 Inspection of boilers and machinery.

109.209 Appliances for watertight integrity.

109.211 Testing of emergency lighting and power systems.

109.213 Emergency training and drills.

109.223 Fire fighting equipment.

109.227 Verification of vessel compliance with applicable stability requirements.

Subpart C—Operation and Stowage of Safety Equipment

109.301 Operational readiness, maintenance, and inspection of lifesaving equipment.

109.323 Manning of survival craft and supervision.

109.329 Fire pumps.