§ 17.49

(b) An extinguishment or improper functioning of a steady burning side intermediate light or lights, shall be corrected as soon as practicable, but notification to the FAA of such extinguishment or improper functioning is not required.

[32 FR 11273, Aug. 3, 1967, as amended at 39 FR 26157, July 17, 1974; 40 FR 30267, July 18, 1975; 61 FR 4364, Feb. 6, 1996; 79 FR 56986, Sept. 24, 2014]

§17.49 Recording of antenna structure light inspections in the owner record.

The owner of each antenna structure which is registered with the Commission and has been assigned lighting specifications referenced in this part must maintain a record of any observed or otherwise known extinguishment or improper functioning of a structure light. This record shall be retained for a period of two years and provided to the FCC or its agents upon request. The record shall include the following information for each such event:

- (a) The nature of such extinguishment or improper functioning.
- (b) The date and time the extinguishment or improper operation was observed or otherwise noted.
- (c) Date and time of FAA notification, if applicable.
- (d) The date, time and nature of adjustments, repairs, or replacements

[48 FR 38477, Aug. 24, 1983, as amended at 61 FR 4364, Feb. 6, 1996; 79 FR 56987, Sept. 24, 20141

§17.50 Cleaning and repainting.

Antenna structures requiring painting under this part shall be cleaned or repainted as often as necessary to maintain good visibility. Evaluation of the current paint status shall be made by using the FAA's In-Service Aviation Orange Tolerance Chart. This chart is based upon the color requirements contained in the National Bureau of Standards Report NBSIR 75-663, Color Requirements for the Marking of Obstructions.

[79 FR 56987, Sept. 24, 2014]

§17.51 [Reserved]

§17.53 Lighting equipment and paint.

The lighting equipment, color or filters, and shade of paint referred to in the specifications are further defined in the following government and/or Army-Navy aeronautical specifications, bulletins, and drawings (lamps are referred to by standard numbers):

TT-P-102 ¹ (Color No. 17875 FS-595).
TT-P-59 ¹ (Color No. 12197, FS-595).
TT-E-489 ¹ (Color No. 12197 FS-595).
MIL-C-250502.
CAA-4463 Code Beacons,
MIL-62732.
L-8103 (FAA AC No. 150/
5345-2 ⁴).
MIL-L-7830 ² .
FAA/DOD L-856 (FAA AC
No. 150/5345-43B4).
No. 116 A21/TS (6,000 h).
No. 125 A21/TS (6,000 h).
No. 620 PS-40 (3,000 h).
No. 700 PS-40 (6,000 h).

¹Copies of this specification can be obtained from the Specification Activity, Building 197, Room 301, Naval Weapons Plant, 1st and N Streets, SE., Washington, D.C. 20407.
²Copies of Military specifications can be obtained by contacting the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Ave., Attention: NPPC-105, Philadelphia Pa 19120.

Forms Center, 5801 Tabor Ave., Attention: NPPC-105, Philadelphia, Pa. 19120.

3 Copies of Federal Aviation Administration specifications may be obtained from the Chief, Configuration Control Branch, AAF-110, Department of Transportation, Federal Aviation Administration, 800 Independence Avenue SW., Washington, D.C. 20591.

⁴Copies of Federal Aviation Administration advisory circulars may be obtained from the Department of Transportation, Publications Section, TAD-443.1, 400 7th St. SW., Washington, D.C. 20590.

[33 FR 11540, Aug. 14, 1968, as amended at 40 FR 30267, July 18, 1975]

§17.54 Rated lamp voltage.

To insure the necessary lumen output by obstruction lights, the rated voltage of incandescent lamps used shall correspond to be within 3 percent higher than the voltage across the lamp socket during the normal hours of operation.

[42 FR 54826, Oct. 11, 1977]

§17.56 Maintenance of lighting equipment.

Replacing or repairing of lights. automatic indicators or automatic control or alarm systems shall be accomplished as soon as practicable.

[79 FR 56986, Sept. 24, 2014]