

§ 22.367

structure owners are responsible for registering antenna structures with the FCC if required by part 17 of this chapter, and for installing and maintaining any required marking and lighting. However, in the event of default of this responsibility by an antenna structure owner, each FCC permittee or licensee authorized to use an affected antenna structure will be held responsible by the FCC for ensuring that the antenna structure continues to meet the requirements of part 17 of this chapter. See § 17.6 of this chapter.

(a) *Marking and lighting.* Antenna structures must be marked, lighted and maintained in accordance with Part 17 of this chapter and all applicable rules and requirements of the Federal Aviation Administration.

(b) *Maintenance contracts.* Antenna structure owners (or licensees and permittees, in the event of default by an antenna structure owner) may enter into contracts with other entities to monitor and carry out necessary maintenance of antenna structures. Antenna structure owners (or licensees and permittees, in the event of default by an antenna structure owner) that make such contractual arrangements continue to be responsible for the maintenance of antenna structures in regard to air navigation safety.

[61 FR 4365, Feb. 6, 1996]

§ 22.367 Wave polarization.

Public mobile station antennas must be of the correct type and properly installed such that the electromagnetic emissions have the polarization required by this section.

(a) *Vertical.* Waves radiated by the following must be vertically polarized:

(1) Base, mobile, dispatch, and auxiliary test transmitters in the Paging and Radiotelephone Service;

(2) Transmitters in the Offshore Radiotelephone Service;

(3) Transmitters on channels in the 72-76 MHz frequency range;

(4) Base, mobile and auxiliary test transmitters in the Cellular Radiotelephone Service;

(5) Control and repeater transmitters on channels in the 900-960 MHz frequency range;

(6) Rural subscriber stations communicating with base transmitters in the

47 CFR Ch. I (10-1-00 Edition)

Paging and Radiotelephone Service pursuant to § 22.563.

(7) Ground and airborne mobile transmitters in the Air-ground Radiotelephone Service.

(b) *Horizontal.* Waves radiated by transmitters in the Public Mobile Services, other than transmitters required by paragraph (a) of this section to radiate a vertically polarized wave must be horizontally polarized, except as otherwise provided in paragraphs (c) and (d) of this section.

(c) *Circular.* If communications efficiency would be improved and/or interference reduced, the FCC may authorize transmitters other than those listed in paragraphs (a)(1) through (a)(7) of this section to radiate a circularly polarized wave.

(d) *Any polarization.* Public Land Mobile stations transmitting on channels higher than 960 MHz are not limited as to wave polarization.

§ 22.371 Disturbance of AM broadcast station antenna patterns.

Public Mobile Service licensees that construct or modify towers in the immediate vicinity of AM broadcast stations are responsible for measures necessary to correct disturbance of the AM station antenna pattern which causes operation outside of the radiation parameters specified by the FCC for the AM station, if the disturbance occurred as a result of such construction or modification.

(a) *Non-directional AM stations.* If tower construction or modification is planned within 1 kilometer (0.6 mile) of a non-directional AM broadcast station tower, the Public Mobile Service licensee must notify the licensee of the AM broadcast station in advance of the planned construction or modification. Measurements must be made to determine whether the construction or modification affected the AM station antenna pattern. The Public Mobile Service licensee is responsible for the installation and continued maintenance of any detuning apparatus necessary to restore proper non-directional performance of the AM station tower.

(b) *Directional AM stations.* If tower construction or modification is planned within 3 kilometers (1.9 miles)