

§ 25.134

service within 6 months after coordination has been completed. Each licensee or registrant must file with the Commission a certification that the facility is completed and operating as provided in paragraph (b) of this section, with the exception of certification of antenna patterns.

[56 FR 24016, May 28, 1991, as amended at 58 FR 68059, Dec. 23, 1993; 59 FR 53327, Oct. 21, 1994]

§ 25.134 Licensing provisions of Very Small Aperture Terminal (VSAT) networks.

(a) All applications for digital VSAT networks with a maximum outbound downlink EIRP density of +6.0 dBW/4 kHz per carrier and earth station antennas with maximum input power density of -14 dBW/4 kHz and maximum hub EIRP of 78.3 dBW will be processed routinely. All applications for analog VSAT networks with maximum outbound downlink power densities of +13.0 dBW/4 kHz per carrier and maximum antenna input power densities of -8.0 dBW/4 kHz shall be processed routinely in accordance with Declaratory Order in the Matter of Routine Licensing of Earth Stations in the 6 GHz and 14 GHz Bands Using Antennas Less than 9 Meters and 5 Meters in Diameter, Respectively, for Both Full Transponder and Narrowband Transmissions, 2 FCC Rcd 2149 (1987) (Declaratory Order).

(b) Each applicant for digital and/or analog VSAT network authorization proposing to use transmitted satellite carrier EIRP densities in excess of +6.0 dBW/4 kHz and +13.0 dBW/4 kHz, respectively, and/or maximum antenna input power densities of -14.0 dBW/4 kHz and maximum hub EIRPs of 78.3 dBW and -8.0 dBW/4 kHz per carrier, respectively, shall conduct an engineering analysis using the Sharp, Adjacent Satellite Interference Analysis (ASIA) program. Applicants shall submit a complete description of those baseline parameters they use in conducting their analysis and tabular summaries of the ASIA program's output detailing potential interference shortfalls. Applicants shall also submit a narrative summary which must indicate whether there are margin shortfalls in any of the current baseline services as a re-

47 CFR Ch. I (10-1-00 Edition)

sult of the addition of the new applicant's high power service, and if so, how the applicant intends to resolve those margin shortfalls. Applicants shall submit link budget analyses of the operations proposed along with a detailed written explanation of how each uplink and each transmitted satellite carrier density figure is derived. Applicants shall provide proof by affidavit that all potentially affected parties acknowledge and do not object to the use of the applicant's higher power density.

(c) Licensees authorized pursuant to paragraph (b) of this section shall bear the burden of coordinating with any future applicants or licensees whose proposed compliant VSAT operations, as defined by paragraph (a) of this section, is potentially or actually adversely affected by the operation of the non-compliant licensee. If no good faith agreement can be reached, however, the non-compliant licensee shall reduce its power density levels to those compliant with the VSAT Order or the Declaratory Order, whichever is applicable.

(d) An application for VSAT authorization shall be filed on FCC Form 312, Main Form and Schedule B. A VSAT licensee applying to renew its license must include on FCC Form 405, the number of constructed VSAT units in its network.

[56 FR 66001, Dec. 20, 1991, as amended at 62 FR 5929, Feb. 10, 1997]

§ 25.135 Licensing provisions for earth station networks in the non-voice, non-geostationary mobile-satellite service.

(a) Each applicant for a blanket earth station license in the non-voice, non-geostationary mobile-satellite service shall demonstrate that transmitter operations will not cause unacceptable interference to other authorized users of the spectrum, based on existing system information publicly available at the Commission at the time of filing, and will comply with operational conditions placed upon the systems with which they are to operate in accordance with § 25.142(b). This demonstration shall include a showing as to all the technical parameters, including duty cycle and power limits,