

§ 25.204

shall be made prior to, or simultaneously with, the filing of the application with the Commission. The notification shall state the geographical coordinates of the antenna (NAD-83 datum), antenna height above ground, ground elevation at the antenna, antenna directivity and gain, proposed frequency and FCC Rule Part, type of emission, effective radiated power, and whether the proposed use is itinerant. Generally, submission of the information in the technical portion of the FCC license application is adequate notification. In addition, the applicant shall indicate in its application to the Commission the date notification was made to the Arecibo Observatory.

(2) After receipt of such applications, the Commission will allow the Arecibo Observatory a period of 20 days for comments or objections in response to the notification indicated. The applicant will be required to make reasonable efforts in order to resolve or mitigate any potential interference problem with the Arecibo Observatory and to file either an amendment to the application or a modification application, as appropriate. If the Commission determines that an applicant has satisfied its responsibility to make reasonable efforts to protect the Observatory from interference, its application may be granted.

(3) The provisions of this paragraph do not apply to operations that transmit on frequencies above 15 GHz.

(j) Applicants for non-geostationary 1.6/2.4 GHz Mobile-Satellite Service/Radiodetermination satellite service feeder links in the bands 17.7-20.2 GHz and 27.5-30.0 GHz shall indicate the frequencies and spacecraft antenna gain contours towards each feeder-link earth station location and will coordinate with licensees of other fixed-satellite service and terrestrial-service systems sharing the band to determine geographic protection areas around each non-geostationary mobile-satellite service/radiodetermination satellite service feeder-link earth station.

(k) An applicant for an earth station that will operate with a geostationary satellite or non-geostationary satellite in a shared frequency band in which the non-geostationary system is (or is proposed to be) licensed for feeder

47 CFR Ch. I (10-1-00 Edition)

links, shall demonstrate in its applications that its proposed earth station will not cause unacceptable interference to any other satellite network that is authorized to operate in the same frequency band, or certify that the operations of its earth station shall conform to established coordination agreements between the operator(s) of the space station(s) with which the earth station is to communicate and the operator(s) of any other space station licensed to use the band.

[30 FR 7176, May 28, 1965, as amended at 36 FR 2562, Feb. 6, 1971; 38 FR 8573, Apr. 4, 1973; 42 FR 8329, Feb. 9, 1977; 44 FR 77167, Dec. 31, 1979; 50 FR 40862, Oct. 7, 1985; 58 FR 13419, Mar. 11, 1993; 58 FR 44904, Aug. 25, 1993; 59 FR 53329, Oct. 21, 1994; 61 FR 8477, Mar. 5, 1996; 61 FR 9945, Mar. 12, 1996; 61 FR 44181, Aug. 28, 1996; 62 FR 55531, Oct. 27, 1997; 65 FR 38325, June 20, 2000]

§ 25.204 Power limits.

(a) In bands shared coequally with terrestrial radio communication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station operating in frequency bands between 1 and 15 GHz, shall not exceed the following limits except as provided for in paragraph (c) of this section:

+40 dBW in any 4 KHz band for $\theta < 0^\circ$
+40+3 θ dBW in any 4 KHz band for $0^\circ < \theta \leq 05^\circ$

where θ is the angle of elevation of the horizon viewed from the center of radiation of the antenna of the earth station and measured in degrees as positive above the horizontal plane and negative below it.

(b) In bands shared coequally with terrestrial radio-communication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station operating in frequency bands above 15 GHz shall not exceed the following limits except as provided for in paragraph (c) of this section:

+64 dBW in any 1 MHz band for $\theta < 0^\circ$
+64+3 θ dBW in any 1 MHz band for $0^\circ < \alpha < 5^\circ$

where θ is as defined in paragraph (a) of this section.

(c) For angles of elevation of the horizon greater than 5° there shall be no restriction as to the equivalent

isotropically radiated power transmitted by an earth station towards the horizon.

(d) Notwithstanding the e.i.r.p. and e.i.r.p. density limits specified in the station authorization, each earth station transmission shall be conducted at the lowest power level that will provide the required signal quality as indicated in the application and further amended by coordination agreements.

(e) For operations at frequencies above 10 GHz, earth station operators may exceed the uplink e.i.r.p. and e.i.r.p. density limits specified in the station authorization under the conditions of uplink fading due to precipitation by an amount not to exceed 1 dB above the actual amount of monitored excess attenuation over clear sky propagation conditions. The e.i.r.p. levels shall be returned to normal as soon as the attenuating weather pattern subsides. The maximum power level for power control purposes shall be coordinated between and among adjacent satellite operators.

(f) The e.i.r.p. of any emission from an earth station operating in the frequency band 13.75-14.0 GHz shall be at least 68 dBW and shall not exceed 85 dBW, with a minimum antenna diameter of 4.5 meters; except in the frequency band 13.772-13.778 GHz, where the e.i.r.p. shall be at least 68 dBW and shall not exceed 71 dBW per 6 MHz, with a minimum antenna diameter of 4.5 meters. Automatic power control may be used to increase the e.i.r.p. density above 71 dBW per 6 MHz to compensate for rain attenuation to the extent that the power flux density at the fixed-satellite space station does not exceed the value resulting from use of 71 dBW per 6 MHz e.i.r.p. in clear sky conditions.

(g) All earth stations in the Fixed Satellite Service in the 20/30 GHz band shall employ uplink adaptive power control or other methods of fade compensation such that the earth station transmissions shall be conducted at the power level required to meet the desired link performance while reducing the level of mutual interference between networks.

[48 FR 40255, Sept. 6, 1983, as amended at 58 FR 13420, Mar. 11, 1993; 61 FR 52307, Oct. 7, 1996; 62 FR 61457, Nov. 18, 1997]

§ 25.205 Minimum angle of antenna elevation.

Earth station antennas shall not normally be authorized for transmission at angles less than 5° measured from the horizontal plane to the direction of maximum radiation. However, upon a showing that the transmission path will be seaward and away from land masses or upon special showing of need for lower angles by the applicant, the Commission will consider authorizing transmissions at angles between 3° and 5° in the pertinent directions. In certain instances, it may be necessary to specify minimum angles greater than 5° because of interference considerations.

[48 FR 40255, Sept. 6, 1983]

§ 25.206 Station identification.

The requirement for transmission of station identification is waived for all radio stations licensed under this part with the exception of satellite uplinks carrying broadband video information which are required to incorporate ATIS in accordance with the provisions set forth under § 25.308 of these rules.

[55 FR 21551, May 25, 1990]

§ 25.207 Cessation of emissions.

Space stations shall be made capable of ceasing radio emissions by the use of appropriate devices (battery life, timing devices, ground command, etc.) that will ensure definite cessation of emissions.

§ 25.208 Power flux density limits.

(a) In the band 3700-4200 MHz, the power flux density at the Earth's surface produced by emissions from a space station for all conditions and for all methods of modulation shall not exceed the following values:

- 152 dB(W/m²) in any 4 kHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;
- $152 + (\delta - 5)/2$ dB(W/m²) in any 4 kHz band for angles of arrival δ (in degrees) between 5 and 25 degrees above the horizontal plane; and
- 142 dB(W/m²) in any 4 kHz band for angles of arrival between 25 and 90 degrees above the horizontal plane

These limits relate to the power flux density which would be obtained under