

transmissions would interrupt a single consecutive speech, play, religious service, symphony, concert, or any type of production. In such cases, the identification transmissions shall be made at the first interruption in the program continuity and at the conclusion thereof. Hourly identification may be accomplished either by transmission of the station or system call sign and unit designator assigned to the individual station or identification of an associated broadcasting station or network with which the remote pickup broadcast station is being used.

(c) In cases where an automatic relay station is a part of the circuit, the call sign of the relay transmitter may be transmitted automatically by the relay transmitter or by the remote pickup broadcast base or mobile station that actuates the automatic relay station.

(d) Automatically activated equipment may be used to transmit station identification in International Morse Code, provided that the modulation tone is 1200 Hz±800 Hz, the level of modulation of the identification signal is maintained at 40%±10%, and that the code transmission rate is maintained between 20 and 25 words per minute.

(e) For stations using the F3Y emission, identification shall be transmitted in the unscrambled analog (F3) mode or in International Morse Code pursuant to the provisions of (d) of this section at intervals not to exceed 15 minutes. For purposes of rule enforcement, all licensees using F3Y emissions shall provide, upon request by the Commission, a full and complete description of the encoding methodology they currently use.

NOTE: Stations are encouraged to identify using their associated part 73 station call sign.

[41 FR 29686, July 19, 1976, as amended at 47 FR 9220, Mar. 4, 1982; 52 FR 47569, Dec. 15, 1987; 56 FR 28499, June 21, 1991]

### Subpart E—Aural Broadcast Auxiliary Stations

#### § 74.501 Classes of aural broadcast auxiliary stations.

(a) *Aural broadcast STL station.* A fixed station for the transmission of aural program material between the

studio and the transmitter of a broadcasting station other than an international broadcasting station.

(b) *Aural broadcast intercity relay (ICR) station.* A fixed station for the transmission of aural program material between radio broadcast stations, other than international broadcast stations, between FM radio broadcast stations and their co-owned FM booster stations, between noncommercial educational FM radio stations and their co-owned noncommercial educational FM translator stations assigned to reserved channels (Channels 201 to 220), between FM radio stations and FM translator stations operating within the coverage contour of their primary stations, or for such other purposes as authorized in § 74.531.

(c) *Aural broadcast microwave booster station.* A fixed station in the broadcast auxiliary service that receives and amplifies signals of an aural broadcast STL or intercity relay station and retransmits them on the same frequency.

[28 FR 13716, Dec. 14, 1963, as amended at 49 FR 7129, Feb. 27, 1984; 53 FR 4169, Feb. 12, 1988; 55 FR 50692, Dec. 10, 1990; 57 FR 41111, Sept. 9, 1992]

#### § 74.502 Frequency assignment.

(a) Except as provided in US 302, broadcast auxiliary stations licensed as of November 21, 1984, to operate in the band 942–944 MHz<sup>1</sup> may continue to operate on a co-equal primary basis to other stations and services operating in the band in accordance with the Table of Frequency Allocations. These stations will be protected from possible interference caused by new users of the band by the technical standards specified in § 101.105(c)(2).

(b) The frequency band 944–952 MHz is available for assignment to aural STL and ICR stations. AM and FM broadcast stations shall have primary use of the band; however, TV broadcast stations may be licensed on a secondary, noninterference basis. One or more of the following 25 kHz segments may be

<sup>1</sup>NOTE: In addition to this band, stations in Puerto Rico may continue to be authorized on 942.5, 943.0, 943.5, 944.0 MHz in the band 942–944 MHz on a primary basis to stations and services operating in accordance with the Table of Frequency Allocations.

§ 74.502

47 CFR Ch. I (10–1–00 Edition)

stacked to form a channel which may be assigned with a maximum authorized bandwidth of 300 kHz except as noted below. The channel, will be assigned by its center frequency, channel bandwidth, and emission designator. The following frequencies are the centers of each segment:

- 944.0125, 944.0375, 944.0625, 944.0875, 944.1125, 944.1375, 944.1625, 944.1875, 944.2125, 944.2375, 944.2625, 944.2875, 944.3125, 944.3375, 944.3625, 944.3875, 944.4125, 944.4375, 944.4625, 944.4875, 944.5125, 944.5375, 944.5625, 944.5875, 944.6125, 944.6375, 944.6625, 944.6875, 944.7125, 944.7375, 944.7625, 944.7875, 944.8125, 944.8375, 944.8625, 944.8875, 944.9125, 944.9375, 944.9625, 944.9875, 945.0125, 945.0375, 945.0625, 945.0875, 945.1125, 945.1375, 945.1625, 945.1875, 945.2125, 945.2375, 945.2625, 945.2875, 945.3125, 945.3375, 945.3625, 945.3875, 945.4125, 945.4375, 945.4625, 945.4875, 945.5125, 945.5375, 945.5625, 945.5875, 945.6125, 945.6375, 945.6625, 945.6875, 945.7125, 945.7375, 945.7625, 945.7875, 945.8125, 945.8375, 945.8625, 945.8875, 945.9125, 945.9375, 945.9625, 945.9875, 946.0125, 946.0375, 946.0625, 946.0875, 946.1125, 946.1375, 946.1625, 946.1875, 946.2125, 946.2375, 946.2625, 946.2875, 946.3125, 946.3375, 946.3625, 946.3875, 946.4125, 946.4375, 946.4625, 946.4875, 946.5125, 946.5375, 946.5625, 946.5875, 946.6125, 946.6375, 946.6625, 946.6875, 946.7125, 946.7375, 946.7625, 946.7875, 946.8125, 946.8375, 946.8625, 946.8875, 946.9125, 946.9375, 946.9625, 946.9875, 947.0125, 947.0375, 947.0625, 947.0875, 947.1125, 947.1375, 947.1625, 947.1875, 947.2125, 947.2375, 947.2625, 947.2875, 947.3125, 947.3375, 947.3625, 947.3875, 947.4125, 947.4375, 947.4625, 947.4875, 947.5125, 947.5375, 947.5625, 947.5875, 947.6125, 947.6375, 947.6625, 947.6875, 947.7125, 947.7375, 947.7625, 947.7875, 947.8125, 947.8375, 947.8625, 947.8875, 947.9125, 947.9375, 947.9625, 947.9875, 948.0125, 948.0375, 948.0625, 948.0875, 948.1125, 948.1375, 948.1625, 948.1875, 948.2125, 948.2375, 948.2625, 948.2875, 948.3125, 948.3375, 948.3625, 948.3875, 948.4125, 948.4375, 948.4625, 948.4875, 948.5125, 948.5375, 948.5625, 948.5875, 948.6125, 948.6375, 948.6625, 948.6875, 948.7125, 948.7375, 948.7625, 948.7875, 948.8125, 948.8375, 948.8625, 948.8875, 948.9125, 948.9375, 948.9625, 948.9875, 949.0125, 949.0375, 949.0625, 949.0875, 949.1125, 949.1375, 949.1625, 949.1875, 949.2125, 949.2375, 949.2625, 949.2875, 949.3125, 949.3375, 949.3625, 949.3875, 949.4125, 949.4375, 949.4625, 949.4875, 949.5125, 949.5375, 949.5625, 949.5875, 949.6125, 949.6375, 949.6625, 949.6875, 949.7125, 949.7375, 949.7625, 949.7875, 949.8125, 949.8375, 949.8625, 949.8875, 949.9125, 949.9375, 949.9625, 949.9875, 950.0125, 950.0375, 950.0625, 950.0875, 950.1125, 950.1375, 950.1625, 950.1875, 950.2125, 950.2375, 950.2625, 950.2875, 950.3125, 950.3375, 950.3625, 950.3875, 950.4125, 950.4375, 950.4625, 950.4875, 950.5125, 950.5375, 950.5625, 950.5875, 950.6125, 950.6375, 950.6625, 950.6875, 950.7125, 950.7375, 950.7625, 950.7875, 950.8125, 950.8375, 950.8625, 950.8875, 950.9125, 950.9375, 950.9625, 950.9875, 951.0125, 951.0375, 951.0625, 951.0875, 951.1125,

- 951.1375, 951.1625, 951.1875, 951.2125, 951.2375, 951.2625, 951.2875, 951.3125, 951.3375, 951.3625, 951.3875, 951.4125, 951.4375, 951.4625, 951.4875, 951.5125, 951.5375, 951.5625, 951.5875, 951.6125, 951.6375, 951.6625, 951.6875, 951.7125, 951.7375, 951.7625, 951.7875, 951.8125, 951.8375, 951.8625, 951.8875, 951.9125, 951.9375, 951.9625, 951.9875.

(1) A single broadcast station may be authorized up to a maximum of twenty segments (500 kHz total bandwidth) for transmission of program material between a single origin and one or more designations. The station may lease excess capacity for broadcast and other uses on a secondary basis, subject to availability of spectrum for broadcast use. However, an FM station licensed for twelve or fewer segments (300 kHz total bandwidth) or an AM station licensed for eight or fewer segments (200 kHz total bandwidth) may lease excess capacity for broadcast and other uses on a primary basis.

(2) An applicant (new or modification of existing license) may assume the cost of replacement of one or more existing licensees equipment with narrowband equipment of comparable capabilities and quality in order to make available spectrum for its facilities. Existing licensees must accept such replacement without cost to them except upon a showing that the replacement equipment does not meet the capability or quality requirements.

(c) Aural broadcast STL and intercity relay stations that were licensed or had applications pending before the Commission as of September 18, 1998 may continue those operations in the band 18,760–18,820 and 19,100–19,160 MHz on a shared co-primary basis with other services under parts 21, 25, and 101 of this chapter until June 8, 2010. Prior to June 8, 2010, such stations are subject to relocation by licensees in the fixed-satellite service. Such relocation is subject to the provisions of §§101.85 through 101.97 of this chapter. After June 8, 2010, such operations are not entitled to protection from fixed-satellite service operations and must not cause unacceptable interference to fixed-satellite service station operations. No new licenses will be granted in these bands.

(1)(i) 5 MHz maximum authorized bandwidth channels:

Federal Communications Commission

§ 74.531

| Transmit (receive) (MHz) | Receive (transmit) (MHz) |
|--------------------------|--------------------------|
| 340 MHz Separation       |                          |
| 18762.5 .....            | 19102.5                  |
| 18767.5 .....            | 19107.5                  |
| 18772.5 .....            | 19112.5                  |
| 18777.5 .....            | 19117.5                  |
| 18782.5 .....            | 19122.5                  |
| 18787.5 .....            | 19127.5                  |
| 18792.5 .....            | 19132.5                  |
| 18797.5 .....            | 19137.5                  |
| 18802.5 .....            | 19142.5                  |
| 18807.5 .....            | 19147.5                  |
| 18812.5 .....            | 19152.5                  |
| 18817.5 .....            | 19157.5                  |

| Transmit (receive) (MHz) | Receive (transmit) (MHz) |
|--------------------------|--------------------------|
| 340 MHz Separation       |                          |
| 18762.5 .....            | 19102.5                  |
| 18767.5 .....            | 19107.5                  |
| 18772.5 .....            | 19112.5                  |
| 18777.5 .....            | 19117.5                  |
| 18782.5 .....            | 19122.5                  |
| 18787.5 .....            | 19127.5                  |
| 18792.5 .....            | 19132.5                  |
| 18797.5 .....            | 19137.5                  |
| 18802.5 .....            | 19142.5                  |
| 18807.5 .....            | 19147.5                  |
| 18812.5 .....            | 19152.5                  |
| 18817.5 .....            | 19157.5                  |

(ii) Licensees may use either a two-way link or one frequency of a frequency pair for a one-way link and shall coordinate proposed operations pursuant to the procedures required in § 101.103(d) of this chapter.

(2) [Reserved]

(d) [Reserved]

(e) The use of the frequencies listed in paragraph (b) of this section by aural broadcast intercity relay stations is subject to the condition that no harmful interference is caused to other classes of stations operating in accordance with the Table of Frequency Allocations contained in § 2.106 of this chapter.

[28 FR 13716, Dec. 14, 1963, as amended at 48 FR 50332, Nov. 1, 1983; 49 FR 37777, Sept. 26, 1984; 50 FR 4658, Feb. 1, 1985; 50 FR 7341, Feb. 22, 1985; 50 FR 34150, Aug. 23, 1985; 50 FR 48600, Nov. 26, 1985; 54 FR 10329, Mar. 13, 1989; 54 FR 24905, June 12, 1989; 54 FR 30043, July 18, 1989; 65 FR 38325, June 20, 2000; 65 FR 54172, Sept. 7, 2000]

EFFECTIVE DATE NOTE: At 65 FR 54172, Sept. 7, 2000, § 74.502(c) was revised, effective Oct. 10, 2000. For the convenience of the user, the superseded text appears as follows:

§ 74.502 Frequency assignment.

\* \* \* \* \*

(c) The frequency bands 18,760–18,820 MHz and 19,100–19,160 MHz are available for assignment to aural broadcast STL and intercity relay stations and are shared on a co-primary basis with other fixed services under Parts 78 and 101 of the Commission's rules.

(1) 5 MHz maximum authorized bandwidth channels:

Applicants may use either a two-way link or one frequency of a frequency pair for a one-way link and shall coordinate proposed operations pursuant to the procedures required in § 101.103(d).

\* \* \* \* \*

§ 74.503 Frequency selection.

(a) Each application for a new station or change in an existing station shall be specific with regard to frequency. In general, the lowest suitable frequency will be assigned which, on an engineering basis, will not cause harmful interference to other stations operating in accordance with existing frequency allocations.

(b) Where it appears that interference may result from the operation of a new station or a change in the facilities of an existing station, the Commission may require a showing that harmful interference will not be caused to existing stations or that if interference will be caused the need for the proposed service outweighs the loss of service due to the interference.

[28 FR 13716, Dec. 14, 1963]

§ 74.531 Permissible service.

(a) An aural broadcast STL station is authorized to transmit aural program material between the studio and transmitter location of a broadcasting station, except an international broadcasting station, for simultaneous or delayed broadcast.

(b) An aural broadcast intercity relay station is authorized to transmit aural program material between broadcasting stations, except international broadcasting stations, for simultaneous or delayed broadcast.