

**§ 74.882**

(3) Any form of modulation may be used. A maximum deviation of ±75 kHz is permitted when frequency modulation is employed.

(4) The frequency tolerance of the transmitter shall be 0.005 percent.

(5) The operating bandwidth shall not exceed 200 kHz.

(6) The mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

(i) On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB;

(ii) On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB;

(iii) On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth: at least  $43+10\log_{10}$  (mean output power in watts) dB.

(f) Unusual transmitting antennas or antenna elevations shall not be used to deliberately extend the range of low power auxiliary stations beyond the limited areas defined in § 74.831.

(g) Low power auxiliary stations shall be operated so that no harmful interference is caused to any other class of station operating in accordance with Commission's rules and regulations and with the Table of Frequency Allocations in part 2 thereof.

(h) In the event a station's emissions outside its authorized frequency band causes harmful interference, the Commission may, at its discretion, require the licensee to take such further steps as may be necessary to eliminate the interference.

(Sec. 5, 48 Stat. 1068; 47 U.S.C. 155)

[43 FR 13576, Mar. 31, 1978, as amended at 52 FR 2535, Jan. 23, 1987; 63 FR 36605, July 7, 1998]

**§ 74.882 Station identification.**

Call signs will not be assigned to low power auxiliary stations. In lieu thereof, for transmitters used for voice transmissions and having a transmitter output power exceeding 50 mW, an announcement shall be made at the beginning and end of each period of op-

**47 CFR Ch. I (10-1-00 Edition)**

eration at a single location, over the transmitting unit being operated, identifying the transmitting unit designator, its location, and the call sign of the broadcasting station or name of the licensee with which it is being used. A period of operation may consist of a continuous transmission or intermittent transmissions pertaining to a single event.

[42 FR 14729, Mar. 16, 1977]

**Subpart I—Instructional Television Fixed Service**

SOURCE: 28 FR 13731, Dec. 14, 1963, unless otherwise noted.

**§ 74.901 Definitions.**

*Attended operation.* Operation of a station by a designated person on duty at the place where the transmitting apparatus is located with the transmitter in the person's plain view.

*Booster service area.* A geographic area to be designated by an applicant for a booster station, within which the booster station shall be entitled to protection against interference as set forth in this part. The booster service area must be specified by the applicant so as to not overlap the booster service area of any other booster authorized to or proposed by the applicant. However, a booster station may provide service to receive sites outside of its booster service area, at the licensee's risk of interference. The booster station must be capable of providing substantial service within the designated booster service area.

*Channel.* Unless otherwise specified, a channel under this part shall refer to a 6 MHz frequency block assigned pursuant to §§ 21.901(b) of this chapter or 74.902(a).

*Documented complaint.* A complaint that a party is suffering from non-consensual interference. A documented complaint must contain a certification that the complainant has contacted the operator of the allegedly offending facility and tried to resolve the situation prior to filing. The complaint must then specify the nature of the interference, whether the interference is constant or intermittent, when the interference began and the site(s) most