aircraft radio operator license may be issued by such foreign government.

EMERGENCY LOCATOR TRANSMITTERS

§87.193 Scope of service.

Transmissions by emergency locator transmitters (ELTs) are intended to be actuated manually or automatically and operated automatically as part of an aircraft or a survival craft station as a locating aid for survival purposes.

§87.195 121.5 MHz ELTs.

ELTs that operate only on frequency 121.5 MHz will no longer be certified. The manufacture, importation, and sale of ELTs that operate only on frequency 121.5 MHz is prohibited beginning July 10, 2019. Existing ELTs that operate only on frequency 121.5 MHz must be operated as certified.

[83 FR 63812, Dec. 12, 2018]

§87.197 ELT test procedures.

ELT testing must avoid outside radiation. Bench and ground tests conducted outside of an RF-shielded enclosure must be conducted with the ELT terminated into a dummy load.

§87.199 Special requirements for 406.0–406.1 MHz ELTs.

(a) 406.0–406.1 MHz ELTs use G1D emission. Except for the spurious emission limits specified in §87.139(h), 406.0-406.1 MHz ELTs must meet all the technical and performance standards contained in the Radio Technical Commission for Aeronautics document titled "Minimum Operational Performance Standards 406 MHz Emergency Locator Transmitters (ELT)" Document No. RTCA/DO-204 dated September 29, 1989. The Director of the Federal Register approves this incorporation by reference in accordance with 5 U.S.C 552(a) and 1 CFR part 51. Copies of this standard can be inspected at the Federal Communications Commission's Reference Information Center, located at the address of the FCC's main office indicated in 47 CFR 0.401(a), Tel: (202) 418-0270, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/ federal_register/code_of_fed-

47 CFR Ch. I (10–1–22 Edition)

eral_regulations/ibr_locations.html. Copies of the RTCA standards also may be obtained from the Radio Technical Commission for Aeronautics, Inc., 1150 18th Street NW., Suite 910, Washington, DC 20036.

(b) The 406.0-406.1 MHz ELT must contain as an integral part a homing beacon operating only on 121.500 MHz that meets all the requirements described in the RTCA Recommended Standards document described in paragraph (a) of this section. The 121.500 MHz homing beacon must have a continuous duty cycle that may be interrupted during the transmission of the 406.0-406.1 MHz signal only.

(c) As part of its Supplier's Declaration of Conformity a 406.0-406.1 MHz ELT, the ELT must be certified by a test facility recognized by one of the COSPAS/SARSAT Partners that the equipment satisfies the design characteristics associated with the COSPAS/ SARSAT document COSPAS/SARSAT 406 MHz Distress Beacon Type Approval Standard (C/S T.007). Additionally, an independent test facility must certify that the ELT complies with the electrical and environmental standards associated with the RTCA Recommended Standards.

NOTE 1 TO PARAGRAPH (c): The verification procedure has been replaced by Supplier's Declaration of Conformity. Equipment previously authorized under subpart J of part 2 of this chapter may remain in use. See §2.950 of this chapter.

(d) The procedures for Supplier's Declaration of Conformity are contained in subpart J of part 2 of this chapter.

(e) An identification code, issued by the National Oceanic and Atmospheric Administration (NOAA), the United States Program Manager for the 406.0-406.1 MHz COSPAS/SARSAT satellite system, must be programmed in each ELT unit to establish a unique identification for each ELT station. With each marketable ELT unit the manufacturer or grantee must include a postage pre-paid registration card printed with the ELT identification code addressed to: NOAA/SARSAT Beacon Registration, NSOF, E/SPO53, 1315 East West Hwy, Silver Spring, MD 20910-9684. The registration card must request the owner's name, address, telephone, type of aircraft, alternate