(f) Conveyors. (1) Conveyors used in the preparation of ready-to-cook poultry shall be of metal or other acceptable material and of such construction as to permit easy identification of the vicsera with their carcass and so designed as will present each carcass or all parts thereof in a way that will permit adequate and efficient inspection.

(2) Overhead conveyors shall be so constructed and maintained that they will not allow grease, oil, or dirt to accumulate on the drop chain or shackle, which shall be of noncorrosive metal.

(3) Nonmetallic belt-type conveyors used in moving poultry products shall be of waterproof composition.

(4) When eviscerated on a conveyor, each carcass shall be suspended and a trough or other acceptable facilities for maintaining proper sanitation shall be provided beneath the conveyor. Such troughs or other facilities shall be flushed or cleaned in an acceptable manner and shall extend beneath the conveyor at all places where processing operations are conducted from the point where the carcass is opened to the point where the viscera have been completely removed.

(g) Chilling and thawing tanks. Chilling and thawing tanks shall be constructed of metal or other suitable material impervious to moisture and shall be of sanitary construction with edges rolled outward. Where mechanical devices are not used for removing carcasses from the chilling or thawing tanks, the tanks will be of a size that will enable employees to remove poultry without entering the tanks.

(h) Tables. Inspection, eviscerating, and cutting tables shall be made of metal or other acceptable material, have coved corners, and be constructed and placed so as to permit thorough cleaning.

(i) Plants lacking conveyors. In plants where no conveyors are used, each carcass shall be eviscerated in an individual metal tray of seamless construction or in a tray of other acceptable material and construction.

(j) Water spray washing equipment. Water spray washing equipment with sufficient water pressure to thoroughly and efficiently wash carcasses inside and out.

9 CFR Ch. III (1–1–00 Edition)

(k) Offal receptacles. Watertight receptacles constructed of metal or other acceptable impervious material shall be used for entrails and other waste resulting from preparation of eviscerated poultry.

(I) Receptacles for condemned carcasses. Watertight receptacles for holding or handling condemned carcasses or parts of carcasses shall be so constructed as to be readily and thoroughly cleaned; such receptacles shall be marked in a conspicuous manner with the words "U.S. Condemned" in letters not less than 2 inches high and when required by the inspector in charge, shall be equipped with facilities for locking and sealing.

[40 FR 60053, Dec. 31, 1975, as amended at 62 FR 45026, Aug. 25, 1997]

§381.54 Accessibility of equipment.

(a) *General.* All equipment shall be placed so as to be readily accessible for all processing and cleaning operations.

(b) *Mechanical pickers*. When mechanical pickers are used, they shall be installed so as to be accessible for thorough cleaning and removal of the accumulation of feathers.

§381.55 Restrictions on use of equipment and utensils.

Equipment and utensils used in the official establishment shall not be used outside the official establishment, except under conditions prescribed or approved by the Administrator in specific cases. Equipment used in the preparation of any article (including, but not limited to, animal food), from inedible material shall not be used outside of the inedible products department except under such conditions as may be prescribed or approved by the Administrator in specific cases.

§381.56 Maintenance of sanitary conditions and precautions against contamination of poultry products; PCB-containing equipment.

(a) The premises of the official establishment shall be kept free from refuse, waste materials, and all other sources of odors and conditions that may result in adulteration of the poultry products handled at the establishment.

(b) New or replacement equipment or machinery (including any replacement