

placed on a rotatable table that is one meter in height. Any excess length of the power cord and other connecting leads shall be coiled on the floor under the table. The EUT shall be immersed in a horizontally polarized uniform CW field of 100 mV/m at a frequency 2.55 MHz above the visual carrier of the EUT tuned channel. Measurements shall be made with the EUT tuned to six EIA IS-132 channels, two each in the low VHF, high VHF and UHF broadcast bands. On each channel, the levels at the IF passband due to the desired and interfering signals are to be measured.

(4) *Tuner overload.* Spurious signals within the IF passband shall be attenuated at least 55 dB below the visual carrier of the desired channel using a comb-like spectrum input with each visual carrier signal individually set at + 15 dBmV from 54 to 550 MHz. The desired input signal is to be an NTSC signal on which the visual carrier is modulated with a 10 IRE flat field with color burst and the aural carrier is unmodulated and 10 dB below the visual carrier. Measurements shall be made with the receiver tuned to at least seven evenly spaced EIA IS-132 channels covering the band 54 MHz to 550 MHz. In addition, spurious signals within the IF passband shall be attenuated at least 51 dB below the visual carrier of the desired channel using a comb spectrum input with each signal individually set at + 15 dBmV from 550 to 804 MHz. Measurements shall be made with the receiver tuned to at least three evenly spaced EIA IS-132 channels covering the band 550 MHz to 804 MHz.

(5) *Cable input conducted emissions.* (i) Conducted spurious emissions that appear at the cable input to the device must meet the following criteria. The input shall be an NTSC video carrier modulated with a 10 IRE flat field with color burst at a level of 0 dBmV and with a visual to aural ratio of 10 dB. The aural carrier shall be unmodulated. The peak level of the spurious signals will be measured using a spectrum analyzer connected by a directional coupler to the cable input of the equipment under test. Spurious signal levels must not exceed the limits in the following table:

From 54 MHz up to and including 300 MHz-	26 dBmV
From 300 MHz up to and including 450 MHz-	20 dBmV
From 450 MHz up to and including 804 MHz-	15 dBmV

(ii) The average of the measurements on multiple channels from 450 MHz up to and including 804 MHz shall be no greater than -20 dBmV. Measurements shall be made with the receiver tuned to at least four EIA IS-132 channels in each of the above bands. The test channels are to be evenly distributed across each of the bands. Measurements for conducted emissions caused by sources internal to the device are to be made in a shielded room. Measurements for conducted emissions caused by external signal sources shall be made in an ambient RF field whose field strength is 100 mV/m, following the same test conditions as described in paragraph (c)(3) of this section.

(d) The field strength of radiated emissions from cable ready consumer electronics equipment shall not exceed the limits in §15.109(a) when measured in accordance with the applicable procedures specified in §§ 15.31 and 15.35 for unintentional radiators, with the following modifications. During testing the NTSC input signal level is to be + 15 dBmV, with a visual to aural ratio of 10 dB. The visual carrier is to be modulated by a 10 IRE flat field with color burst; the aural carrier is to be unmodulated. Measurements are to be taken on six EIA IS-132 channels evenly spaced across the required RF input range of the equipment under test.

[59 FR 25341, May 16, 1994, as amended at 61 FR 18509, Apr. 26, 1996; 65 FR 64391, Oct. 27, 2000; 68 FR 68546, Dec. 9, 2003; 69 FR 2849, Jan. 21, 2004; 69 FR 57861, Sept. 28, 2004; 77 FR 4913, Feb. 1, 2012]

#### § 15.119 [Reserved]

#### § 15.120 Program blocking technology requirements for television receivers.

(a) Effective July 1, 1999, manufacturers of television broadcast receivers as defined in section 15.3(w) of this chapter, including personal computer systems meeting that definition, must ensure that one-half of their product models with picture screens 33 cm (13 in) or larger in diameter shipped in